

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7773)

Set a stone 12x9x5 ins., 8" in the ground for 1/4 sec. cor. mkd. 1/4 on N. face; from which

A Fir 5" dia., bears S.41 1/4°W., 35 1/2 lks. dist. mkd. 1/4 S BT.

A Maple 4" dia., bears N.47 3/4°W., 57 lks. dist. mkd. 1/4 S BT.

Survey by Burton W. Holt - Wit: H.Sohn - Aug. 1965 - C.S. File 51/320

Found - Orig. 12"x9"x5" stone marked 1/4 on N. face.

Set 1/2" x 39" Iron pipe, from which

New BTs- 9" D.Fir bears N.24 1/2°W., 5.2 ft. mkd. 1/4 S6 BT.

21" D.Fir bears S.34 1/2°E., 15.4 ft., from face, mkd. 1/4 S7 BT.

Both trees bark scribed.

This corner lies on steep East slope between two small gulches.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63-56

Found - Iron pipe at 1/4 corner.

9" D.Fir N.24 1/2°W., 5.2 ft., bark scribed 1/4 S6 BT.

21" D.Fir S.34 1/2°E., 15.4 ft., bark scribed 1/4 S7 BT.

Dist. to face on above trees.

Set Brass cap alongside I.P. at cor. mkd:

County Surveyors Office

T 31 S R 3 W

1/4 S 6
S 7

1966

Reblazed and rescribed trees:

9" D.Fir N.24 1/2°W., 5.5 ft. scribed 1/4 S6 CS BT.

21" D.Fir S.34 1/2°E., 16.5 ft. scribed 1/4 S7 CS BT.

BLM Resurvey by Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, Under Group #'s 1277 & 1315, Surveyed Sept. 1985/August 1986 - (DCSO records Vol. 48 Page(s) 18334)

The 1/4 sec. cor., perpetuated and recorded by Holt in 1965, further perpetuated and recorded by Powell in 1966, monumented with an iron post, 1 1/4" dia., firmly set, projecting 16" above ground with 1966 brass cap attached from which the remains of an original bearing tree

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir snag 27" dia., bears S.39½°W., 40 lks. dist., with opened blaze, no marks visible. (Rec. S.41¼°W., 35½ lks.)
and the remains of bearing trees mkd. by Holt
A Fir snag 20" dia., bears S.35 3/4°E., 25 lks. dist. with scribe marks ¼ S7 CS BT visible on partially healed double blaze.
A Fir 14" dia., bears N.20½°W., 8 lks. dist. with healed blaze.
and a new bearing tree
A Fir 6" dia., bears S.32¼°W., 37 lks. dist. mkd. ¼ S7 BT.

Mark Smalley - R. McManis - 11/19/2002 - C.S. file 65/44-25

Found - 1/2" iron pipe, 1¼" iron pipe with brass cap and orig. stone.
27" Fir snag bears S.39°E., 26.4 ft.
20" Fir snag bears S.36°E., 16.5 ft.
20" Fir with healed face bears N.21°W., 5.3 ft.
14" Fir with healed face bears S.32°W., 24.4 ft.
New - 12" D.Fir bears N.65°E., 4.1 ft. scribed "¼ S6 BT"
9" D.Fir bears S.41°E., 25.7 ft. scribed "¼ S7 BT"
Compass decl. 19°E.
Note - 1/2" iron pipe & quartz stone alongside iron pipe with brass cap.