

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7687)

Set post cor. to secs. 5, 6, 31 and 32, from which
A Pine 30" dia., bears N.80°E., 117 lks. dist.
A Fir 20" dia., bears S.22°E., 90 lks. dist.
A Pine 36" dia., bears S.30°W., 30 lks. dist.
A Fir 30" dia., bears N.20°W., 50 lks. dist.

George Wenderoth - Aug. 1942 - C.S. File 46/133

Found - BT, S.22°E., 59.4 ft., standing.
Pine stump mkd. BT, N.80°E., 47 lks. instead of 117 lks.
Pine stump, S.30°W., approx. 30 lks., had been rooted up, no marks.
Set 1" Iron rod, 2 ft. long for corner.
New BT - 14" Fir N.57°10'W., 140.8 ft.

George Wenderoth, Deputy Co. Surveyor - Wit: Frank Loso - June 1950 - M 27-15

Drive 1½" Iron pipe, from which
36" Fir S.22°E., 59.4 ft., Orig. BT.
12" Fir N.46°45'E., 33.8 ft.
15" Fir S.40°24'W., 223.2 ft.
14" Fir N.66°47'W., 140.3 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-45

Found - I.Pipe at section corner.
12" Fir snag, N.46½°E., 33.0 ft. bearing should be N.49°E., scribed "32".
14" Fir stump N.66½°W., 104.3 ft., bearing should be N.65°W., 140.0 ft., scribing visible.
Orig. 36" Fir S.22°E., 59.4 ft., bearing should be S.20°E., bark scribe "BT" and other faint scribing visible.
No trace SW. BT.

Set brass cap alongside I.P. at cor. mkd:
$$\begin{array}{r} R3W \quad T31S \quad \underline{S31} \quad \underline{S32} \\ \quad \quad T32S \quad S \quad 6 \quad S \quad 5 \end{array}$$
 County Surveyors Office
1965

New BTs- 15" Fir S.12°E., 31.3 ft. scribed T32S R3W S5 CS BT
4" Pine S.35°W., 24.6 ft. scribed S6 CS BT.

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec Cor for 31 & 32; 5 & 6, T32-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>6" Pine N.38°W., 17.0 ft. scribed S31 CS BT. 28" Fir N.16°W., 94.0 ft. scribed T31S R3W S31 CS BT</p>
<p>Leonard Herzstein, U.S.F.S. (Deputized, DCSO) -Wit: Tom Wolford - July 1, 1981 - C.S. File 61/27-8 ----- Found 1" I.P. with brass cap, firmly set, projecting 10" above ground, properly mkd., and a 1 3/4" I.P. alongside, from which 36" D.Fir, orig. BT, bears S.22°E., 59.4 ft. to face with scribe marks BT visible on bark blaze. 17" D.Fir bears S.12°E., 31.3 ft. with healed double blaze 9" P.Pine bears S.35°W., 24.1 ft. (Rec. 24.6 ft.) with healed double blaze. 13" P.Pine bears N.38°W., 16.7 ft. (Rec. 17.0 ft.) with healed double blaze. 22" D.Fir stump bears N.16°W., 95.0 ft. (Rec. 94.0 ft.) with healed blaze. New BT: 10" P.Pine bears N.30°E., 16.6 ft. scribed "T31S R3W S32 CS BT" on a double blaze. Corner is 50 ft. East of BLM Snow Creek access road.</p>
<p>Found OK by T. Hostetter, July 2001 - M138-67</p>