

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7692)

Set ¼ sec. post, from which
A Pine 12" dia., bears S.65°E., 38 lks. dist.
A Cedar 20" dia., bears S.48°W., 45 lks. dist.

George J. Wenderoth - Aug. 1942 - (No record source found)

Found Cedar BT, S.48°W., 29.7 ft. still standing and Pine stump in place but rotted, no marks showing.
Set ¾" Iron pipe for corner and mark new tree for BT:
A 12" Cedar N.79°15'E., 38.6 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63-51

Found - ¾" Iron pipe at ¼ corner.
38" Cedar, now stump, S.48°W., 29.7 ft., scribe visible.
12" Cedar now 16", N.79°E., 38.6 ft. scribed "¼ S BT" visible.
Set Brass cap alongside Iron pipe and marked:
County Surveyors Office
T 31 S R 3 W
¼ S 31 | S 32
1966
New BT - 17" Cedar S.69°W., 51.2 ft. scribed ¼ S31 CS BT.

Fd. OK, Aug. 1991 by G. Nygren - M 114-7

Tony Hostetter - For: Seneca Jones Timber Co. - July 2001 - M 138-67

Found - 1966 brass cap & BTs as described in C.S. 52/63
New BTs- 18" Fir, scribed "S32 ¼ BT" bears S.31°E., 27.3 ft. to spike. Measured to the head of 6" spikes placed in root collars (below face.) BT tag.
14" Fir, scribed "S31 ¼ BT" bears N.49°W., 7.5 ft.

Found OK by R. Wytcherley, Dec. 2003 - M143-63