

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7764)

Set a post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face; from which

A Fir 30" dia., bears S.57¼°E., 34½ lks. dist. mkd. ¼ S BT.

A Laurel 13" dia., bears S.37¼°W., 53 lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. -
Wit: R.G. Boyd - Nov. 4, 1959 - C.S. File 42/392-34

Determined by O.B.T.s:

40" Fir snag S.57°E., 22.4 ft.

At corner point found 1" x 30" Iron pipe, from which

16" Laurel bears N.89°E., 21.7 ft. mkd. ¼ S20 BT.

13" Fir bears N.10°E., 16.0 ft. mkd. ¼ S19 BT.

32" Cedar bears S.5°W., 4.4 ft. mkd. ¼ S19 BT.

5" Fir bears N.75°W., 13.8 ft. mkd. ¼ S19 BT.

24" Fir bears West, 43.8 ft. mkd. ¼ S19 CS BT.

Road bears North 210.0 ft.

Fd. OK, Feb. 1981 by H. Johnstone - M 86-42

Fd. OK, Aug. 1985 by H. Johnstone - M 99-36