

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7764-65)

Set a stone 14x8x8 ins., 9" in the ground for cor. to secs. 17, 18, 19 and 20 marked with 5 notches on E. and 3 notches on S. edges; from which

- A Laurel 9" dia., bears N.45½°E., 51½ lks. dist. mkd. T31S R3W S17 BT.
- A Laurel 7" dia., bears S.19°E., 11 lks. dist. mkd. T31S R3W S20 BT.
- A Laurel 8" dia., bears S.30½°W., 28 lks. dist. mkd. T31S R3W S19 BT.
- A Laurel 6" dia., bears N.22°W., 8½ lks. dist. mkd. T31S R3W S18 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Oct. 26. 1959 - C.S. File 42/392-33

Determined by O.B.T:

- 13" dead Laurel snag, bears S.30°W., 18.5 ft.
- At corner point, Set 1¼" x 36" Iron pipe, from which
- 30" Fir bears S.20°E., 14.5 ft. mkd. S20 R3W BT.
- 24" Fir bears S.9°W., 15.0 ft. mkd. S19 BT.
- 6" Maple bears N.82°W., 8.0 ft. mkd. S18 BT.
- 8" Fir bears N.43°E., 18.5 ft. mkd. S17 T31S BT.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Dec. 17, 1980 - M 86-42

- Found - 10" rotten Madrone stump, scribed, bears N.52°E., 36.6 ft. (Rec. N.45½°E.)
18" Madrone S.13°E., 7.3 ft. (Rec. S.19°E.)
Set 5/8" x 30" Iron rod and alum. cap.
New BTs- 12" Madrone N.12°W., 48.6 ft.
22" Fir N.70°E., 15.0 ft.
15" Fir S.81°E., 22.0 ft.
8" Fir S.63°W., 28.0 ft.
Markham's 1¼" I.P. bears S.5°24'34"W., 121.97 ft.