

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7767-68)

Set a stone 13x10x5 ins., 9" in the ground for cor. to secs. 7, 8, 17 and 18, marked with 5 notches on E. and 4 notches on S. edges; from which

A Laurel 8" dia., bears N.70 3/4°E., 7 3/4 lks. dist. mkd. T31S R3W S8 BT.

A Laurel 5" dia., bears S.49 1/2°E., 76 lks. dist. mkd. T31S R3W S17 BT.

A Laurel 6" dia., bears S.53 1/2°W., 13 3/4 lks. dist. mkd. T31S R3W S18 BT.

A Laurel 6" dia., bears N.27°W., 65 1/4 lks. dist. mkd. T31S R3W S7 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Nov. 16, 1959 - C.S. File 42/392-39

Determined by O.B.T.s:

11" Laurel N.27°W., 44.0 ft., found scribe.

16" Laurel N.71°E., 5.3 ft., I rescribed R3W S8 T31S BT.

12" Laurel S.53°W., 9.3 ft., I remarked S18 BT.

At corner point found stone and Set 3/4" x 30" Iron pipe from which

8" Chinquapin bears N.11°W., 27.0 ft. mkd. S7 R3W BT.

12" Fir bears N.53°W., 17.9 ft. mkd. S7 R3W BT.

14" Fir bears S.60°E., 23.7 ft. mkd. S17 BT.

12" Laurel bears S.33°E., 17.0 ft. mkd. S17 T31S R3W BT.

Fd. OK, Feb.1981 by H. Johnstone - M 86-42