

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7770)

Set a stone 12x10x7 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Fir 9" dia., bears N.30°W., 12 lks. dist. mkd. ¼ S BT.
A Hemlock 10" dia., bears N.46¼°E., 10 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors office - Karen Reed; Frank Silagy, crew with Wit: Burt Holt, Sun Studs - May 22, 1979 - C.S. File 60/24-33

Found - A 10" x 6" x 7" stone marked "¼".
9" Fir now 10" snag bears N.20°W., 7.9 ft. with chopped out blaze visible "BT" (Rec. N.30°W.) Orig. BT.
10" Hemlock now 18", bears N.46°E., 6.6 ft. well healed single blaze. Orig. BT.
Set a 1" x 36" I.Pipe with brass cap mkd. "Douglas Co. Surveyor T31S 1/4 S7 S8 R3W 1979" at proper dist. and brg. from Hemlock and dist. from Fir. Placed stone West side of cap 8" underground.
New BTs- 19" D.Fir bears S.52½°W., 16.7 ft. with double blaze scribed "¼ S7 CS BT"
15" D.Fir bears S.43½°E., 24.9 ft. with double blaze scribed "¼ S8 CS BT"
13" Hemlock bears N.61 3/4°W., 26.0 ft. double blaze scribed "¼ S7 CS BT"