

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7773-74)

Set a stone 12x10x5 ins., 8" in the ground, for ¼ sec. cor. marked ¼ on W. face; from which
A Fir 16" dia., bears S.12½°E., 12 lks. dist. mkd. ¼ S BT.
A Fir 16" dia., bears S.51 ¾°W., 38¼ lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Jan. 16, 1959 - C.S. File 42/392-11

Determined by O.B.T.s:
26" Fir bears S.12°E., 8.0 ft.
22" Fir bears S.52°W., 27.2 ft.
At corner point, Set 1½" x 32" Iron pipe, from which
7" Live Oak bears S.59°E., 25.5 ft. mkd. ¼ S5 BT.
5" Laurel bears N.69°E., 23.8 ft. mkd. ¼ S5 BT.

BLM Resurvey by Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, Under Group #'s 1277 & 1315, Surveyed Sept. 1985/August 1986 - (DCSO records Vol. 48 Page(s) 18335-36)

The ¼ sec. cor. perpetuated and recorded by Markham in 1959, monumented with an iron pipe, 1½" dia., firmly set, projecting 6" above the ground, from which the original bearing trees:

A Fir 25" dia., bears S.10¼°E., 12 lks. dist. with healed blaze. (Rec. S.12½°E.)
A Fir 23" dia., bears S.53°W., 38¼ lks. dist. with healed blaze. (Rec. S.51 ¾°W.)
and bearing trees mkd. by Markham
A Madrone 8" dia., bears N.68¼°E., 31 lks. dist. with fragmentary scribe marks visible on partially healed blaze.
A Live Oak 8" dia., bears S.58½°E., 37 lks. dist. with scribe marks S5 ¼ BT visible on partially healed blaze.

At the corner point
Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, directly over the iron pipe, with brass cap mkd:

T 31 S R 3 W
¼
S 6 | S 5
1985

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.