

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 202700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only, T30-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6780)

Set a stone 12x12x8 ins., 8" in the ground for ¼ sec. cor. marked ¼ on N. face, from which
A Fir 30" dia., bears N.71½°E., 15½ lks. dist. mkd. ¼ S BT
A Live Oak 10" dia., bears S.15°W., 47½ lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Jan. 16, 1959 - C.S. File 42/392-9

Determined by O.B.T.s:
36" Fir bears N.71°E., 10.2 ft.
10" L. O. stump bears S.15°W., 31.2 ft., found scribe.
At corner point, SET 1½" x 30" Iron pipe, from which
9" Laurel bears N.50°E., 52.0 ft. mkd. ¼ S32 X BT.
10" Live Oak bears S.46°E., 41.0 ft. mkd. ¼ S32 BT.
23" Fir bears S.7°E., 38.0 ft. mkd. ¼ S32 BT.
Sec. cor. for 5 & 6, T31-3 bears West 167.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63-41

Found - Iron pipe at ¼ corner.
Orig. 36" D.Fir N.71°E., 10.0 ft., shows good scar.
9" Laurel now 11" N.50°E., 52.0 ft., should be 48.8 ft., scribed ¼ S32 BT.
10" Live Oak now 13" S.46°E., 41.0 ft., should be 34.4 ft., scribed ¼ S32 BT.
23" D.Fir now 25" S.7°E., 38.0 ft., bark scribed ¼ S32 BT.

Set brass cap alongside iron pipe at ¼ corner marked:

County Surveyors Office

T 30 S R 3 W

¼ S 32

T 31 S R 3 W

1966

All trees in good condition.

BLM Resurvey by Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, Under Group #'s 1277 & 1315, Surveyed Sept. 1985/August 1986 - (DCSO records Vol. 48 Page(s) 18321)

The ¼ sec. cor., perpetuated and recorded by Markham in 1959, and further perpetuated and recorded by Powell in 1965, monumented with an iron pipe, 1½" dia., firmly set,
(Cont. Next Page)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

projecting 10" above ground, alongside is an iron post, 1½" dia., firmly set, projecting 12" above ground, with brass cap mkd. in 1965, from which the remains of an original bearing tree:
A Fir snag 30" dia., bears N.71½°E., 15½ lks. dist., with healed blaze.
and bearing trees mkd. by Markham:
A Madrone 14" dia., bears N.45½°E., 71 lks. dist., with healed blaze.
A double Live Oak 14" dia., bears S.44 3/4°E., 50 lks. dist., with healed double blaze.
A Fir 27" dia., bears S.6¼°E., 55 lks. dist. with scribe marks ¼ S32 visible on partially healed blaze.
and a new bearing tree:
A Cedar 12" dia., bears N.21½°W., 42 lks. dist., mkd. ¼ S32 BT.

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCSO records Vol. 57 Pages 22510-1)

The ¼ sec. cor. of sec. 32 only, on the S. bdy. of the Tp., monumented with an iron post, 1½" dia. firmly set, projecting 6" above the ground (alongside of which is the original stone, projecting 3" above the ground, with the marks ¼ visible, and an iron pipe, 1½" dia., firmly set, projecting 6" above the ground), with brass cap (properly) mkd. from which the remains of original bearing trees
A sawed and burnt fir stump, 24" dia., bears N.71½°E., 10.2 ft., with no marks visible.
A roothole bears S.15°W., 31.4 ft., with no trunk remains.
and the remains of bearing trees mkd. by Markham, in 1959
A live oak, 15" dia., bears S.44¾°E., 33.0 ft., with a healed blaze.
A fir, 25" dia., bears S.6¼°E., 36.3 ft., with a healed blaze.
and a bearing tree mkd. by Peterson and Bedell, in 1985-86
A cedar, 15" dia., bears N.21½°W., 27.7 ft., with fragmentary scribe marks visible on a partially healed blaze.