

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page 7693)

Set ¼ sec. post, from which
A Fir 8" dia., bears N.35°W., 18 lks. dist.
A Fir 9" dia., bears S.8°W., 5 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Pgs 7759-60)

The ¼ sec. cor., which is a post, greatly decayed, with marks nearly obliterated, I find the 2 original witness trees. I remove this post and set a Fir post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face; from which
A Fir 8" dia., bears N.35°W., 18 lks. dist. mkd. ¼ S BT.
A Fir 9" dia., bears S.8°W., 5 lks. dist. mkd. ¼ S BT.
These trees are both dead. I mark 2 new witness trees as follows:
A Fir 5" dia., bears N.15¾°W., 29 lks. dist. mkd. ¼ S BT.
A Fir 8" dia., bears S.1¼°W., 30 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - Milo Godfrey & crew - 5/1964 - C.S. File 52/63-6 and C.S. File 52/63-75

Reported as not found.

Survey by Gerald V. Nygren, PLS #1035 - For: Medford Corp. - Aug. 20, 1991 - M 114-7 and C.S. File 63/134

Set by single proportion, a 5/8" x 30" Iron rod with yellow plastic cap mkd. "NYGREN LS1035", extended 3" above ground, from which new BTs:
A 5" D.Fir bears N.6°E., 28.6 ft. scribed "¼ S29 BT".
A 5" D.Fir bears S.58°W., 16.8 ft. scribed "¼ S32 BT".
An 8" D.Fir bears S.48°E., 6.3 ft. scribed "¼ S32 BT".
An 8" D.Fir bears S.23°W., 17.7 ft. scribed "¼ S32 BT".

Fd. Ok by M. Heimburger - 7/2001 - M138-35
Found OK by R. Wytcherley, Dec. 2003 - M143-63