

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7762)

-----  
A Fir 20" dia., for 1/4 sec. cor. which I mark 1/4 S on N. face; from which

A Fir 11" dia., bears S.71 1/4°W., 48 lks. dist. mkd. 1/4 S BT.

A Fir 10" dia., bears N.15°W., 21 1/2 lks. dist. mkd. 1/4 S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: O.A. Keatley - Nov. 4, 1959 - C.S. File 42/392-37

-----  
At corner point found 25" Fir stump and scribed wood post.

I Set 1 1/4" x 36" Iron pipe, from which

14" Cedar bears S.53°E., 37.0 ft. already scribed "1/4 S29 CS BT".

22" Laurel bears S.62°E., 10.0 ft. mkd. 1/4 S29 BT.

10" Laurel bears N.67°E., 26.0 ft. mkd. 1/4 S20 T31S R3W BT.

4" Cedar bears N.5°E., 6.5 ft. mkd. 1/4 S20 BT.

Road bears East 70.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63-67

-----  
Found - Iron pipe out of ground.

14" Cedar now 16", S.53°E., 37.0 ft., scribe visible "BT 1/4 S".

22" Laurel S.62°E., 10.0 ft., bark scribed.

10" Laurel now 12", N.67°E., 26.0 ft., bark scribed.

4" Cedar now 7", N.5°E., 6.5 ft., scribe visible "S"

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

1/4 S 20

S 29

1966

Set brass cap alongside iron pipe.

Reblazed and rescribed:

22" Laurel S.62°E., 10.0 ft. scribed 1/4 S29 CS BT.

12" Laurel N.67°E., 26.0 ft. scribed 1/4 S20 CS BT.

Fd. OK, Sept. 1985 by H. Johnstone - M 99-36