

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7765)

-----  
A Laurel 7" dia., which I mark ¼ S on N. face for ¼ sec. cor., from which

A Laurel 8" dia., bears S.32°E., 17 lks dist., mkd. ¼ S BT.

A Laurel 8" dia., bears S.19°E., 28 ¾ lks. dist. mkd. ¼ S BT.

-----  
Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: O.A. Keatley - Nov. 4, 1959 - C.S. File 42/392-36

-----  
At corner point, Set 1¼" x 40" Iron pipe, from which

5" Cedar bears S.34°E., 7.1 ft., kd. ¼ S20 BT.

11" Fir bears North, 26.9 ft. mkd. ¼ S17 R3W BT.

12" Maple bears S.6°W., 19.2 ft. mkd. ¼ S20 BT.

Top of ridge bears West, 121.0 ft.

-----  
Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Dec. 17, 1980 - M 86-42

-----  
Set 5/8" x 30" Iron rod and alum. cap, from which

8" Fir S.73°W., 10.8 ft.

6" Fir N.21°E., 7.0 ft.

Markham's 1¼" I.P. bears S.67°07'16"W., 111.22 ft.