

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7768)

Set a stone 12x12x4 ins., 8" in the ground for 1/4 sec. cor. mkd. 1/4 on N. face; from which

A Fir 30" dia., bears S.42 1/2°E., 17 3/4 lks. dist. mkd. 1/4 S BT.

A Fir 2" dia., bears N.44 1/2°W., 28 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, Mike Stone, Jack Heritage, crew - April 1966 - C.S. File 52/63-92

Found - No trace of corner stone.

29" Fir now 35", N.44°W., 18.4 ft., opened for scribe "8".

30" Fir now 36", S.42 1/2°E., 11.5 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

1/4 $\frac{S \ 8}{S \ 17}$
1966

New BT - 6" laurel N.28°E., 14.5 ft. scribed 1/4 S8 CS BT.