

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 242700

PRIMARY CORNER DESCRIPTION C C to Secs. 32 & 33 only, T30-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6779)

Set a stone 14x10x4 ins., 10" in the ground for closing cor. to secs. 32 and 33, marked C C on N. face with 4 notches on E. and 2 notches on W. faces, from which

A Fir 16" dia., bears N.75½°E., 13 lks. dist. mkd. T30S R3W S33 BT.

A Fir 22" dia., bears N.41¼°W., 26 lks. dist. mkd. T30S R3W S32 BT.

A Fir 18" dia., bears S.15½°E., 11 lks. dist. mkd. T30S R3W C C S32 and 33 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - June 9, 1960 - C.S. File 42/392-55

Determined by O.B.T.s;

22" dead Fir snag N.75°E., 8.6 ft., found scribe.

Both other BTs burnt off at ground level.

At Corner point found stone and Set 3/4" x 30" I.P., from which

20" Cedar N.7°E., 6.0 ft. "S33 R3W BT".

20" Cedar N.5°W., 22.0 ft. "S32 R3W BT".

20" Cedar S.35°W., 34.0 ft. "S5 T31S X BT".

16" Cedar S.1°W., 34.7 ft. "S5 T31S R3W BT".

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63-47

Found - Iron pipe at sec. corner.

20" Cedar now 22" N.7°E., 6.0 ft., scribing visible.

20" Cedar now 21" N.5°W., 22.0 ft. scribing visible.

20" Cedar now 22" S.35°W., 34.0 ft. scribing visible

16" Cedar now 18" S.1°W., 34.7 ft. scribing visible.

Set Brass cap alongside I.Pipe mkd: County Surveyors Office

T30S R3W

S 32 | S 33

S 5

T31S

All BTs in very good condition.

This corner is now in cutting corner and lies on the West slope of ridge close to small ravine.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Jan. 4, 1989 - C.S. File 62/61-6

Found - A 3/4" inside dia. Iron pipe firmly set and flush with the ground. (Cont. Next Page)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 1¼" O.D. iron pipe with a 2½" dia., DCSO brass cap loosely set protruding 20" above ground. 3/4" I.P. is along South side of DCSO BC/IP.
 Original Stone not seen.
 20" now 20" dia., 6 ft. high Cedar stump with a fully healed double blaze, bears N.7°E., 6.0 ft.
 16" now 18" dia. 6 ft. high Cedar stump with partially healed double blaze, faces are burnt, no scribing visible, bears S.1°W., 34.0 ft. (Rec. S.1°W. 34.7 ft. possible slope measurement.)
 20" now 24" dia., 6 ft. high Cedar stump with a fully healed double blaze bears S.35°W., 31.7 ft. (Rec. S.35°W., 34.0 ft. dist. possible to center of trunk, not root crown.)
 20" now 35" dia. burnt and dead standing Cedar with a fully healed single blaze, bears N.5°W., 22.0'.
 Dirt mounded around BC/IP. Brass cap now protrudes 6" above ground.
 No trees alive or suitable stumps in area to use as BTs or bearing objects.

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2000, 2100, & 2300, surveyed Nov. 2004/Feb. 2005 - (DCSO rec. Vol. 55 Page(s) 21501-4) & 2008-1 thru 2008-4 Plats

 The Closing cor. of secs. 32 & 33 only, on the S bdy of the Tp., perpetuated by Markham in 1960, from orig. evidence no longer in existence, further perpetuated by Powell in 1966, monumented with an iron pipe 1¼" dia., firmly set, projecting 9" above the ground, with brass cap incompletely mkd.

COUNTY SURVEYORS OFFICE
 T30S
S 32 | S 33
 S 5 R3W
 T31S

from which the remains of BTs mkd by Markham
 A burnt cedar snag, 14" dia., bears N.10°E., 6.0 ft. with no marks visible.
 A burnt cedar snag, 7" dia., bears S.2½°E., 31.3 ft. with no marks visible.
 A burnt cedar snag, 17" dia., bears S.36½°W., 32.6 ft., with no marks visible.
 A burnt cedar snag, 16" dia., bears N.3½°W., 22.0 ft., with no marks visible.
 and new accessories
 continued next page

TOWNSHIP 30 RANGE 03 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION C C to Secs. 32 & 33 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A rebar, 30" long, 5/8" dia., driven 28" I the ground for a reference monument, bears N.45°E., 7.50 ft. with alum. cap mkd RM T30S R3W S33 7.5 FT TO COR 2005 and an arrow point to the cor.

A rebar, 30" long, 5/8" dia., driven 28" I the ground for a reference monument, bears N.45°W., 7.50 ft. with alum. cap mkd RM T30S R3W S32 7.5 FT TO COR 2005 and an arrow point to the cor.

Fd. & Used on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCSO records Vol. 57 Page(s) 22509-10)