

PRIMARY CORNER DESCRIPTION Sec Cor for 32 & 33; 4 & 5, T32-3

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7687)

 Set post cor. to secs. 4, 5, 32 and 33, from which
 A Laurel 8" dia., bears N.45°E., 60 lks. dist.
 A Fir 24" dia., bears S.46°E., 68 lks. dist.
 A Fir 16" dia., bears S.34°W., 52 lks. dist.
 A Pine 24" dia., bears N.48°W., 67 lks. dist.

George J. Wenderoth - Aug. 1942 - C.S. File 46/133

 Found - One BT standing, 34" Fir S.34°W., 34.0 ft.
 Found scribe mark "T" on old rotted Laurel stump,
 N.45°E., 39.6 ft.
 New BTs- A 28" Fir N.72°04'E., 30.5 ft.
 A 15" Fir N.31°36'W., 63.2 ft.
 Set a 1" x 33" bolt.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63-46

 Found - Iron bolt at sec. corner.
 28" Fir now 42", N.72°E., 30.5 ft., shows good scar.
 16" Fir now 22", N.31½°W., 63.2 ft., shows good scar
 opened for scribing "S2".
 34" Fir now 38", S.34°W., 34.0 ft., shows good scar.
 Set Brass cap at cor. mkd: County Surveyors Office

		T 31 S	
	R3W	S 32 S 33	
		S 5 S 4	
		T 32 S	
		1966	

New BT - 8" D.Fir N.64°W., 15.0 ft. scribed T31S R3W S32 CS BT.

Survey by William J. Ruppert, L.S. #866 - For: U.S. Forest Service - March 1980 - M 79-28

 Found - 1" galv. I.P. with 2½" brass cap properly stamped.
 1" iron bolt alongside and North.
 42" d.Fir bears S.34°42'W., 34.5 ft. with good scar.
 10" D.Fir bears N.63°20'W., 14.7 ft. with good scars
 28" D.Fir bears N.32°19'W., 62.9 ft. with good scars
 50" D.Fir stump bears N.72°42'E., 31.9 ft. with good scar.

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec Cor for 32 & 33; 4 & 5, T32-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

38" Fir snag bears S.43°46'E., 46.1 ft., 12 ft. high
and rotted.
3 ft. high Pine snag bears N.44°37'W., 44.2 ft.
New BTs- 10" D.Fir bears N.56°16'E., 62.9 ft. scribed T31S
R3W S33 BT.
7" D.Fir bears S.32°52'E., 13.3 ft. scribed T32S R3W
S4 BT.

Fd. OK, Aug. 1991 by G. Nygren - M 114-7