

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol 18 Pages 7748-49)

Set a Fir post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face; from which
A Fir 10" dia., bears N.10°E., 21 lks. dist. mkd. ¼ S BT
A Laurel 30" dia., bears S.85°W., 50 lks. dist. mkd. ¼ S BT.

Douglas Co Surveyors Office - James Byron, Deputy - Milo Godfrey, Clete Putnam, crew - Dec. 22, 1960 - C.S. File 52/63-2

Found - Orig. 10" now 12" Fir N.10°E., 13.9 ft., shows good scribing "¼S".
Orig. 30" now 34" Laurel, shell of snag, shows scribing.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 3 W
¼ S29 | S28
1960

New BT - 17" Cedar bears N.53½°W., 50.4 ft. mkd. ¼ S29 CS BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63-66

Found - Brass cap at ¼ corner.
17" Cedar now 19", N.54°W., 50.4 ft. scribed ¼ S29 CS BT.
Laurel snag, N.40°W.
10" D.Fir now 12", N.10°E., 13.9 ft. scribed "S4"
This tree's face had been badly cut up.

New BT - 8" Cedar N.28°E., 15.7 ft. scribed ¼ S28 CS BT.

Fd. and used in BLM Resurvey by Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, Under Group #'s 1277 & 1315, Surveyed Sept. 1985/August 1986 - (DCSO records Vol. 48 Page(s) 18327-28)

Adam DeGroot - For: Roseburg Resources - Aug. 2016 - M171-14

Found - A 1¼" iron post by DCSO in 1960 per C.S. File 52/63, firmly set & projecting 12" above the ground, w/a properly mkd 2½" brass cap per record: from which
A 23" D.Fir bears N.12°E., 13.8 ft w/healed blaze (N.10°E., 21 lks) Orig
A 31" Cedar bears N.54°45'W., 49.8 ft w/healed dbl blaze (N.53°30'W., 50.4 ft) 1960

continued next page

