

PRIMARY CORNER DESCRIPTION Sec Cor for 20, 21, 28 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7749)

-----  
Set a stone 16x12x8 ins., 12" in the ground, for cor. to secs. 20, 21, 28 and 29, marked with 4 notches on E. and 2 notches on S. edges; from which

A Laurel 15" dia., bears N.39°E., 52½ lks. dist. mkd. T31S R3W S21 BT.

A Laurel 18" dia., bears S.42 3/4°E., 58½ lks. dist. mkd. T31S R3W S28 BT.

A Laurel 11" dia., bears S.18½°W., 29½ lks. dist. mkd. T31S R3W S29 BT.

A Cedar 28" dia., bears N.48 3/4°W., 45 lks. dist. mkd. T31S R3W S20 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone, Wm. Stoffell, Mike Darby, crew - May 21, 1964 - C.S. File 52/63-5

-----  
Found - Rock set in 1894, no marks visible on rock.  
Dead Cedar snag, approx. 15 ft. high, N.48 3/4°W., 29.7 ft., previously opened, scribing visible on old face "31 3 & 20".

32" Madrone S.18½°W., 19.5 ft., scar visible.

24" Madrone N.39°E., 34.5 ft., scar visible.

Portion of rotted Madrone stump, with small Madrone tree growing from one side, S.42 3/4°E., 38.6 ft.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W  
S 20 | S 21  
S 29 | S 28  
1964

Set rock alongside.

New BTs- 16" Hemlock N.12°E., 11.2 ft. mkd T31S R3W S21 CS BT

8" D.Fir N.7°W., 10.3 ft. mkd. S20 CS BT.

12" D.Fir S.77°E., 32.3 ft. mkd. T31S R3W S28 CS BT

Reblaze and scribe:

32" Madrone S.18½°W., 19.5 ft mkd T31S R3W S29 CS BT

Fd. OK, Sept. 1985 by H. Johnstone - M 99-36

BLM Resurvey by Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, Under Group #'s 1277 & 1315, Surveyed Sept. 1985/August 1986 - (DCSO records Vol 48 Pages 18328-29)

-----  
The Sec. cor. perpetuated and recorded by Godfrey in 1964, ...  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 20, 21, 28 and 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

... monumented with an iron post 1½" dia., firmly set, projecting 14" above ground, with 1964 brass cap attached from which the remains of the original bearing trees

- A Madrone 25" dia., bears N.37°E., 52¼ lks., with healed blaze. (Rec. N.39°E.)
- A Madrone 30" dia., bears S.18½°W., 29½ lks. with healed blaze.
- A Cedar snag 37" dia., bears N.48 3/4°W., 47 lks. with illegible scribe marks visible on an opened blaze. (Rec. 45 lks.)

and the remains of the bearing trees mkd. by Godfrey

- A Fir 20" dia., bears N.12°E., 17 lks., with healed blaze.
- A Fir stump 18" dia., bears S.77°E., 48 lks., with scribe mark T visible on an open blaze.
- A Fir 15" dia., bears N.7°W., 16 lks., with healed blaze.

and a new bearing tree

- A Fir 8" dia., bears S.58°E., 17 lks. mkd. T31S R3W S28 BT

Adam DeGroot - For: Roseburg Resources - Aug. 2016 - M171-14  
 -----  
 Found - A 1¼" iron post by DCSO in 1964 per C.S. File 52/63, firmly set & projecting 14" above ground w/a properly mkd 2½" brass cap per record: from which

- A 25" Madrone bears N.38°45'W., 34.7 ft w/healed blaze (N.39°E., 52.5 lks) Orig.
- A 31" Madrone bears S.17°W., 18.5 ft w/scribe mks "S" Visible on partially healed blaze (S.18°30'W., 29.5 lks) Orig.
- A 30" rotted cedar snag bears N.47°45'W., 29.9 ft w/illegible scribe mks visible on opened blaze (N.48°45'W., 45 lks)
- A 18" W.Fir snag bears N.12°45'E., 11.1 ft w/healed dbl blaze (N.12°E., 11.2 ft) 1964
- A rotted fir stump bears S.76°45'E., 32.0 ft (S.77'E., 32.3 ft) 1964
- A 22" D.Fir bears N.9°W., 10.6 ft w/healed blaze (N.7°W., 10.3 ft)
- A BT by BLM in 1986: A 11" W.Fir bears S.56°45'E., 11.0 ft w/healed blaze (S.58°E., 17 lks)

New - A MAGHUB & brass washer set in root crown of 25" D.Fir bears N.44°58'14"E., 57.22 ft.  
 A MAGHUB & brass washer set in root crown of 49" D.Fir bears N.0°20'10"W., 66.92 ft.