

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7751)

Set a stone 14x12x6 ins., 9" in the ground, for 1/4 sec. cor. mkd. 1/4 on W. face; from which
A Yew 9" dia., bears S.74 1/2°W., 30 3/4 lks. dist. mkd. 1/4 S BT.
A Hemlock 12" dia., bears S.54 1/2°E., 44 1/2 lks. dist. mkd. 1/4 S BT.

Survey by Norman D. Price, RE #33 - For: Dollar and Patterson Co., Inc. - April 1955 - C.S. File 41/374

At the corner, a basalt stone is set, 12x6x5 ins. above ground, firmly set, mkd. 1/4 on W. face; from which the remains of original bearing trees:
A burnt Hemlock 16" dia., bears S.54 1/2°E., 44 1/2 lks. dist., on which no marks remain.
A burnt yew 12" dia., bears S.74 1/2°W., 31 lks. dist., on which no marks remain.
and new bearing trees;
A Hemlock 15" dia., bears S.72 1/2°E., 60 lks. dist. mkd. 1/4 S21 RS33 BT.
A Yew 12" dia., bears N.89°W., 76 lks. dist. mkd. 1/4 S20 RS33 BT.
Against North side of stone, Set an iron pipe 3 ft. long, 1 1/2" dia., 28" in the ground, mkd. RS33.

Fd. OK, Sept. 1985 by H. Johnstone - M 99-36

BLM Resurvey by Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, Under Group #'s 1277 & 1315, Surveyed Sept. 1985/August 1986 - (DCSO records Vol. 48 Page(s) 18331)

The 1/4 sec. cor., perpetuated and recorded by Price in 1955, monumented with an iron post 1 1/2" dia., firmly set, projecting 8" above ground, with brass disk mkd. LS33 and with the original basalt stone 12x10x6 ins., mkd. 1/4, lying alongside, from which the remains of the original bearing trees:
A root hole bears S.54 1/2°E., 44 1/2 lks. dist., with a burnt Hemlock stump lying alongside, size indeterminate, no remaining marks.
A root hole bears S.74 1/2°W., 30 3/4 lks. dist., with a burnt Yew alongside, size indeterminate, no remaining marks.
At the corner point

(Cont. Next Page)

