

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7751)

Set a stone 20x12x10 ins., 15" in the ground for cor. to secs. 16, 17, 20 and 21, marked with 4 notches on E. and 3 notches on S. edges; from which

A Fir 32" dia., bears N.44°E., 55 lks. dist., mkd. T31S R3W S16 BT.

A Fir 24" dia., bears S.75½°E., 81 3/4 lks. dist. mkd. T31S R3W S21 BT.

A Fir 36" dia., bears S.11°W., 20½ lks. dist. mkd. T31S R3W S20 BT.

A Laurel 6" dia., bears N.69¼°W., 28 lks. dist. mkd. T31S R3W S17 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: O.A. Keatley - Nov. 4, 1959 - C.S. File 42/392-35

Determined by O.B.T.s:

30" Fir N.44°E., 36.3 ft.

42" Fir S.75°E., 54.0 ft.

38" Fir stump, logged, S.11°W., 13.5 ft.

11" Laurel N.69°W., 18.5 ft., I rescribed S17 T31S R3W BT.

At corner point found stone and Set 1¼" x 48" iron pipe, from which

12" Laurel bears S.59°W., 3.5 ft. mkd. S20 R3W BT.

7" Cedar bears S.79°E., 8.5 ft. mkd. X S21 X BT.

7" Cedar bears N.12°E., 38.5 ft. mkd. S16 R3W BT.

Fd. OK, Feb. 1981 by H. Johnstone - M 86-42

BLM Resurvey by Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, Under Group #'s 1277 & 1315, Surveyed Sept. 1985/August 1986 - (DCSO records Vol. 48 Page(s) 18332-33)

The Sec. cor., perpetuated and recorded by Markham in 1959, monumented with an iron pipe 1¼" dia., projecting 12" above ground, with the original basalt stone 15x11x6 ins. (Rec. 20x12x10 ins.), set alongside, with 4 notches on the E. and 3 notches on the S. faces, from which the remains of the original bearing trees:

A Fir 42" dia., bears N.44°E., 55 lks. dist., with healed blaze.

A Fir 42" dia., bears S.75½°E., 83 lks. dist., with healed blaze. (Rec. 81 3/4 lks.)

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir stump 46" dia., bears S.11°W., 20½ lks. dist., with healed blaze.

A Madrone 13" dia., bears N.69¼°W., 28 lks. dist., with a rotted out blaze.

and bearing trees mkd. by Markham

A Cedar 17" dia., bears N.12°E., 58½ lks. dist., with two healed blazes.

A Cedar 15" dia., bears S.79°E., 13 lks. dist., with healed blaze.

A Madrone 15" dia., bears S.59°W., 6 lks. dist., with healed blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 3 W
S 17 | S 16
S 20 | S 21
1986

Deposit the original stone and iron pipe alongside and white "DEEP-1" magnetic marker at base of stainless steel post.