

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Pgs 7755-56)

-----  
A Cedar 8" dia., which I mark ¼ S on W. face for ¼ sec. cor., from which

A Laurel 5" dia., bears S.68°W., 22 lks. dist. mkd. ¼ S BT

A Fir 40" dia., bears S.24¾°E., 33¾ lks. dist. mkd. ¼ S BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, Mike Stone, Jack Heritage, crew - April 1966 - C.S. File 52/63-93

-----  
Found - 8" Cedar now 20" at ¼ corner.

40" Fir now 47" bears S.24½°E., 22.1 ft. Opened for scribe "4".

Orig. SW. BT not found.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

¼ S8 | S9

1966

New BT - 17" D.Fir N.88°W., 9.8 ft. scribed ¼ S8 CS BT.