

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7758)

Set a stone 11x11x5 ins., 7" in the ground for 1/4 sec. cor. marked 1/4 on W. face; from which

A Fir 10" dia., bears S.15°E., 16 lks. mkd. 1/4 S BT.

A Laurel 10" dia., bears S.72½°W., 30 lks. mkd. 1/4 S BT.

John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd & O.A. Keatley - May 17, 1960 - C.S. File 42/39251

Determined by O.B.T.s: (Govt. notes had East and West turned around on both original BTs)

12" Laurel S.72°E. 19.8 ft. I rescribed "1/4 S4 T31S R3W BT"

15" Fir S.15°W., 10.6 ft.

At corner point found original stone, from which

38" Fir N.68°W., 25.7 ft. mkd. 1/4 S BT.

3" Chinquapin bears N.61°W., 12.2 ft. mkd. 1/4 S BT.

6" Laurel bears N.6°W., 5.5 ft. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63-72

Found - Stone at 1/4 corner.

38" Fir N.68°W., 25.7 ft., bark scribed "1/4 S5 BT"

3" Chinquapin now 5", N.61°W., 12.2 ft. scribe visible "1/4 S5 BT".

6" Laurel now 7" N.6°W., 5.5 ft. scribe visible "1/4 S BT".

Orig. 12" laurel S.72°E., 19.8 ft., bark scribed.

Orig. 16" Fir S.15°W., 10.6 ft., shows good scr.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

1/4 S5 | S4

1966

All BTs in good condition.

This corner is now cutting corner on steep, North hillside.

BLM Dependent resurvey, rehabilitation, & remonumentation by A. Bert Skeesick, Cadastral Surveyor, and Robert H. Browning, Survey Tech., under Group No. 2000, 2100, 2300 - Surveyed Aug 2005/Feb 2006 - (DCSO rec Vol 55 Pg 21618 & 2009 BLM Plat)

The 1/4 sec. cor. of secs. 4 & 5, perpetuated by Markham. date unknown, further perpetuated by Powell, in 1966, monumented with a basalt stone, 11x11x5", loosely set, projecting 2" above ground, w/marks 1/4 visible on NW face, w/an iron post, 28" long 1 1/4" dia lying loose on the ground alongside cont.

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

with brass cap (properly) mkd.
from which the remains of the orig. BTs
A decayed madrone stump, size indeterminate, bears S.71°E.
19.8 ft., with no marks visible, (Record S.72½°W.)
A fir snag. 18" dia., bears S.16°W., 10.6 ft., with no
marks visible, (Record S.15°E.)
and the remains of BTs mkd. by Markham
A sawed, burnt fir stump. 39" dia., bears N.68°W., 25.2
ft., with no marks visible.
A decayed chinquapin stump, size indeterminate, bears
N.66°W., 12.2 ft., with no marks visible.
A decayed madrone stump, size indeterminate, bears N.6°W.,
5.2 ft., with no marks visible.

At the corner point
Set an iron post, 28 long, 2½" dia., 25" in the ground, with
brass cap marked: T31S R3W
 ¼
 S 5 | S 4
 2005

from which
A fir, 3" dia., bears N.65½°E., 8.6 ft., mkd: X BT.
A chinquapin, 5" dia., bears N.60¼°W., 11.6 ft., mkd: ¼ S5
BT in the bark.

Inverted and bury the orig. basalt stone along the N. side,
bury the iron post horizontally alongside the S. side, and
deposit a magnet in a white plastic case at the base of the
stainless steel post.

The geographic position (NAD 1983) of this cor., as
determined by a differentially corrected code-phase GPS
receiver observation, is as follows:

Latitude: 42°54'28.1"N
Longitude: 123°04'17.9"W