

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 303700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 33 only, T30-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6779)

-----  
Set a stone 14x10x8 ins., 10" in the ground for ¼ sec. cor. marked ¼ on N. face, from which  
A Fir 16" dia., bears N.4½°E., 12 ¾ lks. mkd. ¼ S BT.  
A Fir 5" dia., bears S.72½°E., 28 lks. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: Geo. Vaughn - Aug. 8, 1951 - C.S. File 40/363-3

-----  
Determined by old bearing trees;  
A dead Fir snag 16" dia., bears N.4½°E., 8.0 ft. scribe showing.  
A dead Fir snag 55" dia., bears S.72°E., 18½ ft.  
At corner point, Set 4' x 4' stone, from which  
An Alder 4" dia., bears S.57°E., 12.0 ft. mkd. ¼ S BT.  
A Fir 8" dia., bears S.49°W., 25.0 ft. mkd. ¼ S BT.  
The corner of secs. 4 & 5, T31-3 bears West, approx. 200 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63-49

-----  
Found - No trace of 4' x 4' stone.  
4" Alder now 6" S.57°E., 12.0 ft., opened tree for scribe, found some but tree was too rotten to identify. Also found bearing to be S.37°E.  
8" Fir now 15" S.49°W., 25.0 ft., shows good scars.  
Set Brass cap at cor. mkd: County Surveyors Office  
T30S R3W  
¼ S 33  
T31S R3W  
1966

New BT - 4" Hemlock N.13½°E., 28.0 ft. scribed ¼ S33 CS BT. Corner lies directly under large windfall. Creek bears West about 150 ft. Corner is on E-W cutting line.

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2127 surveyed Feb/April 2006- (DCSO records Vol. 57 Pages 22507-8)

-----  
The ¼ sec. cor. of sec. 33 only, on the S. bdy. of the Tp., perpetuated by Markham, in 1951 from original evidence no longer in existence, further perpetuated by Powell, in 1966, monumented with an iron pipe, 1¼" dia., firmly set, projecting 9" above the ground, with brass cap (properly) mkd

continued next page

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 303700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 33 only, T30-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of bearing trees mkd. by Markham  
A roothole bears S.59½°E., 13.4 ft., with no trunk remains. An alder stump, 8" dia., bears S.37¾°E., 10.4 ft., with no marks visible.  
and new reference monuments  
An iron rod, 30" long, 5/8" dia., driven 27" in the ground, bears N.66°56'13"E., 6.82 ft. with aluminum cap mkd. RM ¼ S33 6.8 FT TO COR 2006 and an arrow pointing to the cor.  
An iron rod, 30" long, 5/8" dia., driven 27" in the ground, bears N.3°04'34"W., 7.90 ft. with aluminum cap mkd. RM ¼ S33 7.9 FT TO COR 2006 and an arrow pointing to the cor.