

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; & 4 of T32-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7688)

-----  
Set ¼ sec. post, from which  
A Pine 36" dia., bears N.15°E., 53 lks. dist.  
A Laurel 6" dia., bears S.58°W., 46 lks. dist.

George J. Wenderoth, Deputy Co. Surveyor - Oct. 1955 - C.S. File 47/17 and M 41-10

-----  
Set from measurement from section corners, 1" Iron pipe, from which I scribe:  
7" Fir N.1°37'E., 24.1 ft.  
14" Fir S.42°05'W., 11.8 ft.  
Old corner is gone.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-44

-----  
Found - Iron pipe at 1/4 cor. and scribed stake.  
11" D.Fir N.1°E., 24.5 ft., shows scribed "BT ¼".  
17" D.Fir S.41°W., 11.0 ft., shows good scars.

Set brass cap alongside I.P. for ¼ cor. marked:

County Surveyors Office  
¼  $\frac{S\ 33}{S\ 4}$  T31S R3W  
T32S  
1966

All trees in good condition.

Fd. OK, Oct. 1994 by R. Templin - M 121-13