

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 340240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by William Ruppert - For: U.S. Forest Service - Feb. 1980 - M 79-29 and C.S. File 58/143 (n)

-----  
Set 2" x 30" alum. pipe with 2½" magnetized alum. cap marked "T31S R3W C 1/4 S28 PLS 866 1980", from which new BTs:  
12" W.Fir bears N.7°15'W., 19.8 ft. "C ¼ S28 BT"  
18" W.Fir bears N.6°18'E., 13.4 ft. mkd. "C ¼ S28 BT".

Fd. and used in BLM Resurvey by Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, Under Group #'s 1277 & 1315, Surveyed Sept. 1985/August 1986 - (DCSO records Vol. 48 Page(s) 18340)

Adam DeGroot - For: Roseburg Resources - Aug. 2016 - M171-14

-----  
Found - A 2½" aluminum post by Ruppert in 1980 Per M 79-29, firmly set flush w/top of 24" dia. stone mound, w/a properly mkd 2½" alum. cap per record: from which BTs by Ruppert in 1980:  
A 21" W.Fir bears N.65°45'E., 13.5 ft w/healed dbl blaze (N.66°18"E., 13.4 ft)  
A 19" W.Fir snag bears N.7°30'W., 19.3 ft w/healed dbl blaze (N.7°15'W., 19.8 ft)  
New BT - A 11" W.Fir bears N.31°W., 34.8 ft scribed "C¼ S28 BT" on dbl blaze  
New RMs- A 5/8"x30" iron rod bears S.46°24'58'E., 26.62 ft.  
A 5/8"x30" iron rod bears S.41°17'09"W., 25.84 ft.