

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7752)

Set a Fir post 4 ft. long, 4" sq., 24" in the ground for 1/4 sec.cor. marked 1/4 S on N. face; from which

A Cedar 20" dia., bears N.45 1/2°E., 31 lks. dist. mkd. 1/4 S BT.

A Fir 32" dia., bears S.27 3/4°W., 8 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, Mike Stone, Jack Heritage, crew - April 1966 - C.S. File 52/63-90

Found - Orig. 20" Cedar now 36", N.45 1/2°E., 20.5 ft., opened for scribe "S".

Orig. 32" Fir now 38", S.27 3/4°W., 5.3 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

1/4 S 16

S 21

1966

New BT - 11" Laurel, North 42.3 ft. scribed 1/4 S16 CS BT.

Corner lies about 125.0 ft. E. of ridge top, location tag on top of ridge on N. side of Laurel.