

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7757)

-----  
Set a stone 12x10x5 ins., 8" in the ground for ¼ sec. cor. marked ¼ on N. face, from which

A Fir 6" dia., bears N.68¼°W., 17 lks. dist. mkd. ¼ S BT

A Laurel 10" dia., bears S.10 3/4°W., 35½ lks. dist. mkd. ¼ S BT.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - June 10, 1982 - M 92-44

-----  
Found - 5"x6"x10" stone marked "¼".

10" Madrone bears S.10 3/4°W., 23.6 ft. Rotten face, partial scribing.

14" Fir bears N.68¼°W., 11.2 ft., healed.

Set 5/8" x 36" iron rod and alum. cap mkd. LS 498.

New BTs- 34" Fir bears S.76°E., 29.3 ft.

23" Fir bears N.16°W., 15.5 ft.