TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 340640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - May 17, 1960 - C.S. File 42/392-53

At corner point, Set 3/4" x 30" iron pipe, from which
30" Fir bears S.74°E., 17.0 ft. mkd. ¼ S4 C.C. BT.
20" Fir bears N.25°E., 12.0 ft. mkd. ¼ S4 C.C. BT.
Top of ridge bears West 120.0 ft.
West 1/4 corner bears West 2667.2 ft.
East 1/4 corner bears East 2415.8 ft.

Survey by Howard Johnstone - For: Roseburg Lumber Co. - June 10, 1982 - M 92-44

Set 5/8" x 36" iron rod, and alum. cap mkd. LS 498, from which new BTs bear:
5" Fir bears N.67°W., 30.6 ft.
4" Fir bears S2°E., 6.8 ft.
Looked for and not found I.R. set by Markham.

Ron Quimby - Crew: N. Fromdahl & J. Ogden - 7/2019 - C.S. File 65/102-68

Found - Alum. Cap on iron pipe mkd:
T31S R3W
C ¼
S 1/4
LS 498 1982
New - 10" fir S.80°W., 15.4 ft. scribed C¼ S4 BT
5' alum post East 5'
Note - Compass decl. 15½°E.