

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 344700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, T30-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6778)

-----  
Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for closing cor. to secs. 33 and 34 marked C C T30S R3W on N.; S34 on E.; and S33 on N. faces, with 3 notches on E. and W. faces, from which

A Fir 16" dia., bears N.13 3/4°E., 48½ lks. dist., marked T30S R3W S34 BT.

A Fir 32" dia., bears N.17½°W., 84½ lks. dist. mkd. T30S R3W S33 BT.

A Fir 17" dia., bears S.71½°E., 30 lks. dist. mkd. T30S R3W S C S33 and 34 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - June 20, 1960 - C.S. File 42/392-60

-----  
Determined by O.B.T.s:

40" Fir S.71°E., 19.8 ft.

20" Fir snag N.14°E., 32.6 ft., found scribe.

At corner point, Set 1½" x 36" Pipe, from which

30" Laurel snag, live, bears S.34°E., 18.0 ft. mkd. S4 T31S R3W BT.

20" Fir N.88°W., 11.4 ft. mkd. S33 T30S BT.

28" Fir S.84°W., 26.8 ft. mkd. S4 T31S R3W BT.

15" Fir S.62°W., 15.8 ft. already scribed.

Corner lies 30 ft. East of top of side ridge.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63-50

-----  
Found - Iron pipe at sec. corner.

Orig. 40" Fir now 41" S.71°E., 19.8 ft. shows good scar.

30" Laurel S.34°E., 18.0 ft. scribed "S4" and bark scribed.

20" D.Fir now 17" N.88°W., 11.4 ft. scribed "S33" visible.

15" D.Fir now 18" S.62°W., 15.8 ft. rotten scribe visible.

28" D.Fir now 29" S.84°W., 26.8 ft., bark scribed.

Set Brass cap at Cor. alongside iron pipe mkd:

County Surveyors Office

T30S R3W

S 33 | S 34

S 4

T31S R3W

1966

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 344700

PRIMARY CORNER DESCRIPTION C C for Secs. 33 & 34 only, T30-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

New BTs reblazed and scribed:  
29" D.Fir S.84°W., 27.5 ft. scribed T31S R3W S4 CS  
BT.  
18" D.Fir S.62°W., 15.8 ft. scribed S4 CS BT.

BLM resurvey by A. Bert Skeesick Cadastral Surveyor & Robert H. Browning, Surveying Tech. under Group #2000, 2100, & 2300, surveyed Nov. 2004/Feb. 2005 - (DCSO rec. Vol. 55 Page(s) 21501-4) & 2008-1 thru 2008-4 Plats

-----  
The closing cor. of secs. 33 & 34 only, on the S. bdy. of the Tp, perpetuated by Markham, further perpetuated by Powell in 1966, monumented with an iron pipe. 1¼" dia. firmly set, badly bent, projecting 12" above the ground (laying on the ground alongside of which is an iron pipe, 24" long, 2" dia., with no cap) with brass cap mkd. COUNTY SURVEYORS OFFICE T30S R3W S33 S34R S4 3W T31S 1966: from which the remains of an orig. BT

- A burnt fir stump, size indeterminate, bears S.71½°E., 19.8 ft. with no marks visible.
- and the remains of BTs mkd by Markham
- A burnt roothole bears S.34°E., 18.0 ft. with no remains visible.
- A burnt fir snag, size indeterminate, bears S.66°W., 15.4 ft. with no marks visible.
- A burnt fir stump, 30" dia., bears S.84°W., 27.4 ft. with a healed blaze.
- A burnt fir snag, size indeterminate, bears N.88°W., 11.9 ft. with no marks visible.

At the corner point  
Drive a finned alum. rod, 36" long, ¾" dia., 35" in the ground, with alum. cap mkd.

T30S R3W  
S 33 | S 34  
S 4  
2004

- from which
- A rebar, 30" long, 5/8" dia., driven 28" I the ground for a reference monument, bears N.48°E., 7.50 ft. with alum. cap mkd RM S34 7.5 FT TO COR 2004 and an arrow point to the cor.
  - A rebar, 30" long, 5/8" dia., driven 28" I the ground for a reference monument, bears N.48°W., 7.50 ft. with alum. cap mkd RM S33 7.5 FT TO COR 2004 and an arrow point to the cor.

Deposit a magnet in a white plastic case, the iron pipe with brass cap and the iron pipe without a cap, alongside the finned alum. rod.

\_\_\_\_\_cont.

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 344700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, T30-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor & Robert H. Browning, Survey Tech, under Group No 2127 surveyed Feb/April 2006- (DCSO records Vol 57 Pgs 22506-7)

-----  
The closing cor. of secs. 33 & 34 only, on the S. bdy. of the Tp., monumented with a finned aluminum rod, 3/4" dia., firmly set, projecting 1" above the ground, with aluminum cap (properly) mkd.

from which the remains of BTs trees mkd. by Markham, in 1960

A burnt and decayed fir snag, 17" dia., bears S.66°W., 15.4 ft., with a healed blaze.

A burnt and decayed fir stump, 34" dia., bears S.84°W., 27.4 ft., with a healed blaze.

A burnt and decayed fir snag, 18" dia., bears N.88°W., 11.9 ft., with a healed blaze.

and reference monuments set by Skeesick and Browning

An iron rod, 5/8" dia., firmly set, projecting 1" above the ground, bears N.48°00'00"E., 7.50 ft. with aluminum cap mkd. RM S34 7.5 FT TO COR 2004 and an arrow pointing to the cor.

An iron rod, 5/8" dia., firmly set, flush with the ground, bears N.48°00'00"W., 7.50 ft. with aluminum cap mkd. RM S33 7.5 FT TO COR 2004 & an arrow pointing to the cor.