

PRIMARY CORNER DESCRIPTION Sec Cor for 33 & 34; 3 & 4, T32-3

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7688)

Set post cor. to secs. 3, 4, 33 and 34, from which
A Fir 16" dia., bears N.30°E., 24 lks. dist.
A Fir 20" dia., bears S.45°E., 23 lks. dist.
A Chinquapin 6" dia., bears S.62°W., 26 lks. dist.
A Fir 24" dia., bears N.58°W., 44 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7733-34)

The Sec. cor., which is a post, greatly decayed, with marks nearly obliterated, I fine 2 of the original witness trees. I remove this post and set a Fir post, 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 3, 4, 33 and 34, mkd. T31S S34 on NE.; R3W S3 on SE.; T32S S4 on SW.; and S33 on NW. faces, with 3 notches on E. and W. edges; from which
A Fir 20" dia., bears S.45°E., 23 lks. dist. mkd. T32S R3W S3 BT.
A Chinquapin 6" dia., bears S.62°W., 26 ks. dist. mkd. T32S R3W S4 BT.
These are the original witness trees. I mark 2 trees as follows:
A Chinquapin 6" dia., bears N.68°E., 29 lks. dist. mkd. T31S R3W S34 BT.
A Fir 10" dia., bears N.51°W., 59 lks. dist. mkd. T31S R3W S33 BT.

George Wenderoth - C.S. File 45/226 & 45/229

1" Iron pipe, from which
30" Fir S.42°55'E., 15.2 ft.
10" Chinquapin S.26°42'W., 14.1 ft.
12" Fir N.75°05'E., 20.7 ft.
12" Hemlock N.59°18'E., 29.4 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan/Feb. 1966 - C.S. File 52/63-70

Found - 1" Iron pipe at section corner.
30" now 34" Fir, S.43°E., 15.2 ft., opened but pitched over. Distance to the face.
10" Chinquapin, now dead, S.26½°W., 14.1 ft. scribe visible.

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec Cor for 33 & 34; 3 & 4, T32-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

12" now 14" Fir N.75°W., 20;7 ft., shows good scar.
12" Hemlock, now blow down, N.59°E., 29.4 ft.,
scribe visible.
Set brass cap at sec. cor. alongside iron pipe, marked:
County Surveyors Office
T 31 S R
S 33 | S 34 3
S 4 | S 3 W
T 32 S
1966
New BTs- 8" D.Fir S.60½°W., 42.9 ft. scribed T32S R3W S4 CS
BT.
13" D.Fir N.35°E., 52.0 ft. scribed T31S R3W S34 CS
BT.
This corner lies on top of small side ridge in bottom of
ravine.

Fd. OK, Oct. 1994 by R. Templin - M 121-13

Dylan Hitner - For: Triple S, LLC - 8/2016 - M172-44

Found - Brass cap
40" Fir bears S.43°E., 15.2' w/tag & face.
18" Fir bears N.75°W., 20.7' w/tag & face.
22" Fir bears N.35°E., 52.0' w/tag & face.
16" Fir bears S.60.5°W., 42.9' w/tag & face.