

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7690)

Marked a Fir 24" dia., for ¼ sec. post.
A Fir 12" dia., bears S.70°E., 9 lks. dist.
A Fir 14" dia., bears S.40°W., 20 lks. dist.

Fd. and Used in GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7734)

George J. Wenderoth, Deputy Co. Surveyor - Nov. 1946 - Wit: Donald Snyder - C.S. File 45/229

Find both original BTs, bearings do not agree but distances do.
Drive 1¼" Pipe for corner. Bend to the NW. on account of root.
A 22" Fir S.50°08'W., 13.2 ft.
A 19" Fir S.59°12'E., 5.94 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-36

Found - 22" D.Fir now 24", S.50°W., 13.2 ft., previously opened for scribe.
19" Fir now 21" S.59°E., 5.9 ft., shows good scar, pitched over.
Iron pipe at ¼ corner.
Set Brass cap alongside iron pipe for ¼ corner marked:
County Surveyors Office
T31S R3W
¼ S 33 | S 34
1965
Both BTs in good condition.