

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 and 34

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7690-91)

Set post, cor. to secs. 27, 28, 33 and 34, from which
A Laurel 12" dia., bears N.45°E., 8 lks. dist.
A Laurel 16" dia., bears S.10°E., 32 lks. dist.
A Fir 6" dia., bears S.35°W., 26 lks. dist.
A Laurel 10" dia., bears N.50°W., 34 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7735)

The Sec. cor., which is a post, greatly decayed, with marks nearly obliterated, I find 3 of the original witness trees. I remove this post and set a Fir post, 4 ft. long, 4" sq., 24" in the ground, for cor. mkd. T31S S27 on NE.; R3W S34 on SE.; S33 on SW.; and S28 on NW. faces, with 3 notches on E. and 1 notch on S. edges; from which
A Laurel stump 4 ft. high bears N.45°E., 8 lks. dist. mkd. T31S R3W S27 BT.
A Laurel 16" dia., bears S.10°E., 32 lks. dist. mkd. T31S R3W S34 BT.
A Fir 6" dia., (9" now) bears S.35°W., 26 lks. dist. mkd. T31S R3W S33 BT.
The Laurel witness tree in sec. 28 is destroyed by fire. I, therefore, mark 2 new witness trees:
A Sugar Pine 10" dia., bears N.15°E., 93½ lks. dist. mkd. T31S R3W S27 BT.
A Laurel 16" dia., bears N.49°W., 78½ lks. dist. mkd. T31S R3W S28 BT.

George J. Wenderoth, Deputy Co. Surveyor - Wit: Donald Snyder - Nov. 1946 - C.S. File 45/229

Find three old BTs.
Drive 1" Pipe for corner.
Scribe - 20" Madrone, S.24°30'E., 39.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan/Feb. 1966 - C.S. File 52/63-78

Found - Iron pipe at sec. cor.
Orig. 12" Laurel N.45°E., 5.3 ft., gone.
Orig. 16" Laurel, rotted out, S.10°E., 21.1 ft.
Orig. 10" Laurel N.50°W., 22.4 ft. gone.
6" Fir now 17" S.35°E., 17.2 ft., shows good scar.
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

16" Laurel now 22", N.47°W., 51.8 ft. Tree opened, scribe visible.
10" Pine now 35", N.15°E., 61.7 ft., shows good scar. (Dist. should be 63.3 ft.)
20" Laurel now 22", S.24½°E., 39.0 ft., scribe visible.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 3 W
S 28 | S 27
S 33 | S 34
1966
New BT - 5" Hemlock N.5°W., 17.9 ft. scribed S28 CS BT.

Survey by Glenn S. Baughman, LS #536 - For: U.S. Forest Service - Oct. 1979 - C.S. File 58/176-31

Found - A 1" I.P., firmly set, projecting 12" above the ground with a 2½" DCSO brass cap, properly mkd.
26" Laurel with center rotted out, bears S.6°E., 21.1 ft. to face. (Rec. S.10°E.) Orig. BT.
15" Fir with healed blaze, bears S.39°W., 17.2 ft. to face. (Rec. S.35°W.) Orig. BT.
35" rotted Sugar Pine stump, with healed blaze, bears N.15°E., 63.4 ft. (Rec. 61.7 ft.)
22" Laurel stump with scribe marks "R3 S28" visible, bears N.49°W., 51.8 ft.
22" Laurel with scribe marks "S 34 BT" visible, bears S.24½°E., 39.0 ft.
New BTs- 12" D.Fir bears N.42°E., 122.1 ft. mkd. "T31S R3W S27 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.
8" D.Fir bears N.8°W., 68.7 ft. mkd. "T31S R3W S28 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.

Fd. and Used in BLM Resurvey by Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, Under Group #'s 1277 & 1315, Surveyed Sept. 1985/August 1986 - (DCSO records Vol. 48 Page(s) 18323)