

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7737)

Set a stone 14x10x8 ins., 9" in the ground for cor. to secs. 21, 22, 27 and 28, marked with 3 notches on E. and 2 notches on S. edges; from which

A Fir 4" dia., bears N.23½°E., 22 lks. dist. mkd. T31S R3W S22 BT.

A Fir 15" dia., bears S.45½°E., 34¼ lks. dist. mkd. T31S R3W S27 BT.

A Laurel 16" dia., bears S.80½°W., 29 lks. dist. mkd. T31S R3W S28 BT.

A Fir 16" dia., bears N.85°W., 46 lks. dist. mkd. T31S R3W S21 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Feb. 1966 - C.S. File 52/63-80

Found - Stone at sec. corner.

Orig. 4" Fir, dead, N.23½°E., 14.5 ft.

Orig. 15" Fir, blow down, S.45½°E., 22.4 ft.

Orig. 16" Laurel, now 24", S.80½°W., 19.1 ft., scribe visible.

Orig. 16" Fir now 22", N.85°W., 30.4 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

S 21 | S 22

S 28 | S 27

1966

New BT - 9" D.Fir N.33½°E., 20.0 ft. scribed T31S R3W S22 CS BT.

No other suitable trees available.

BLM Resurvey by Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, Under Group #'s 1277 & 1315, Surveyed Sept. 1985/August 1986 - (DCSO records Vol. 48 Page(s) 18325)

The sec. cor., perpetuated and recorded by Powell in 1966, monumented with an iron post 1½" dia., firmly set, projecting 10" above ground, (with original sandstone, 14x10x8 ins., lying alongside, with 2 notches on the S. edge and 3 notches on the E. edge,) with 1966 brass cap attached.

from which the remains of the original bearing trees:

A Fir snag 8" dia., bears N.23½°E., 22 lks. dist. with scribe marks T31S R3W S22 BT visible on opened blaze.

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A root hole bears S.45½°E., 34¼ lks. dist., with a rotted Fir 22" dia., lying alongside, no marks remaining.
A Madrone 25" dia., bears S.80½°W., 29 lks. dist., with a rotted blaze.
A Fir 26" dia., bears N.85°W., 46 lks. dist., with healed blaze.
and a bearing tree mkd. by Powell:
A Fir 15" dia., bears N.33½°E., 31 lks. dist., with healed blaze.
and a new bearing tree:
A Fir 4" dia., bears S.28°E., 23½ lks. dist., mkd. X BT.

Fd. BC & 4 BTs by Gregg Neitsch - 6/2022 - M181-10