

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7742)

Set a stone 11x10x6 ins., 7" in the ground for cor. to secs. 9, 10, 15 and 16, marked with 3 notches on E. and 4 notches on S. edges; from which

- A Laurel 10" dia., bears N.12½°E., 84 lks. dist. mkd. T31S R3W S10 BT.
- A Fir 50" dia., bears S.43½°E., 74 lks. dist. mkd. T31S R3W S15 BT.
- A Fir 36" dia., bears S.40½°W., 38½ lks. dist. mkd. T31S R3W S16 BT.
- A Laurel 15" dia., bears N.18 3/4°W., 26½ lks. dist. mkd. T31S R3W S9 BT.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #555, surveyed July/Aug 1964 - (DCSO records Vol. 33 Page(s) 13828)

The Sec. cor., determined at record bearing and distance from the remaining original bearing trees:

- A Madrone clump bears N.12½°E., 84 lks. dist.
- A Fir 66" dia., bears S.43½°E., 74 lks. dist. with a healed blaze.
- A down Fir 42" dia., bears s.50½°W., 38½ lks. dist. with scribe marks T 3 S R visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 3 W
S 9 S 10
S 16 S 15
1964

from which new bearing trees

- A Fir 7" dia., bears N.12°E., 15½ lks. dist. mkd. T31S R3W S10 BT.
- A Fir 10" dia., bears S.9°W., 88½ lks. dist. mkd. T31S R3W S16 BT.
- A Cedar 34" dia., bears N.46°W., 97 lks. dist. mkd. T31S R3W S9 BT.