

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7746)

-----  
Set a stone 12x8x6 ins., 8" in the ground for ¼ sec. cor. marked ¼ on W. face; from which  
A Fir 14" dia., bears N.40½°E., 17 lks. mkd. ¼ S BT.  
A Cedar 11" dia., bears N.35½°W., 39 lks. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - May 17, 1960 - C.S. File 42/392-54

-----  
Determined by O.B.T.s:  
30" Fir N.40°E., 11.2 ft.  
24" Cedar N.35°W., 25.7 ft.  
At corner point, Set 3/4" x 30" Iron pipe, from which  
9" Laurel bears S.51°W., 14.0 ft. mkd. ¼ S4 T31S BT.  
10" Laurel bears S.16°W., 30.5 ft. mkd. ¼ S4 T31S BT  
30" Fir S.2°E., 14.0 ft. mkd. ¼ S3 BT, on bark.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63-71

-----  
Found - Iron pipe as recorded.  
9" laurel, now snag, S.51°W., 14.0ft., scribe visible "¼S4".  
10" Laurel, now stump, S.16°W., 30.5 ft., scribe visible "BT".  
30" Fir S.2°E., 14.0 ft., scribe visible, "¼S 3 BT", bark scribed.  
Orig. 30" Fir N.40°E., 11.2 ft., shows good scar.  
Orig. 24" Cedar now 25", N.35°W., 25.7 ft., shows good scar.

Set Brass cap at cor. alongside iron pipe mkd:  
County Surveyors Office  
T 31 S R 3 W  
¼ S4 | S3  
1966

Reblazed and rescribed:  
30" Fir S.2°E., 14.0 ft. "¼ S3 CS BT"

BLM Dependent resurvey, rehabilitation, & remonumentation by A. Bert Skeesick, Cadastral Surveyor, and Robert H. Browning, Survey Tech. under Group No. 2000, 2100, 2300 - Surveyed Aug 2005/Feb 2006 - (DCSO rec Vol 55 Pg 21618 & 2009 BLM Plat)

-----  
The 1/4 sec. car. of secs. 3 & 4, perpetuated by Markham, it, 1960, remonumented by Powell, in 1966, monumented with an iron post, 1¼" dia. firmly set, projecting 9" above (CONT)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

ground (alongside of which is an iron pipe., 3/4" dia., firmly set, projecting 5" above ground), with brass cap (properly) mkd.  
from which the remains of the original bearing trees  
A sawed, decayed fir stump, 30" dia., bears N.40½°E., 11.2 ft., with no marks visible.  
A cedar snag, 25" dia., bears N.35½°W., 25.7 ft., with a healed blaze.  
and the remains of a bearing tree mkd. by Markham  
A burnt fir snag, 31" dia., bears S.2°E., 14.0 ft., with a healed blaze.  
and new accessories  
A fir, 5" dia., bears N.23½°E., 15.2 ft., mkd: X BT.  
A rebar, 30" long, 5/8" dia., driven 29" in the ground as a reference monument, bears S.43°E., 7.5 ft. with aluminum cap mkd. RM T31S R3W S3 7.5 FT TO COR 2005. and an arrow pointing to the cor.  
A rebar. 30 ins, long, 5/8" dia., driven 27" in the ground as a reference monument, bears S.44°W., 7.4 ft., with aluminum cap mkd. RM T31S R3W S4 7.4 FT TO COP 2005, and on arrow pointing to the cor.  
The geographic position (NAD 1983) of this cor., as determined by a differentially corrected code-phase GPS receiver observation, is as follows:  
Latitude: 42°54'29.0"N  
Longitude: 123°03'09.5"W

Tony Hostetter - For: Rome Crk Timber - Sept. 2015 - M170-20  
-----  
Found - 1966 Douglas Co Surveyor brass cap with 1" iron pipe alongside.  
20" cedar, burnt, no markings, bears; N.35°W., 25.7 ft to center.  
36" fir, burnt, no marks, bears; S.02°E., 14.0 ft to center.  
10" fir, face evident, 2005 BLM tag bears N.23°E., 15.2 ft to center.  
20" fir stump, 2005 BLM tag, bears N.40°E., 11.2 ft to center.  
2" alum cap, 2005 BLM reference monument, bears S.42°E., 7.5 ft.  
2" alum cap, 2005 BLM reference monument, bears S.46°W., 7.4 ft.  
New BT - 8" fir, scribed "S4 ¼ BT", BT tag, bears S.32°W., 17.5 ft to spike.

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ron Quimby - Crew: N. Fromdahl & J. Ogden - 7/2019 - C.S.  
File 65/102-67

-----  
Found - DCS0 Brass Cap (properly mkd.)  
36" fir snag S.2°E., 14.0 ft., no marks.  
12" fir stump N.23°E., 15.2 ft., rotted face.  
20" fir stump N.40°E., 11/2 ft., no marks.  
2" alum. Cap S.42°E., 7.5 ft.  
2" alum. Cap N.46°W., 7.4 ft.  
Down 8" D.Fir S.32°W., 17.5 ft. vis. scribe.  
New - 5' alum. Post N. 5.0 ft.  
5' alum. Post W. 5.0 ft.  
Note - Compass decl. 15½°E.