

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 34; & 3, T32-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7688)

Set 1/4 sec. post, from which
A Laurel 7" dia., bears N.30°E., 26 lks. dist.
A Pine 8" dia., bears S.5°W., 9 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7733)

The 1/4 sec.cor. which is a post, greatly decayed, marked 1/4 S on N. face, I find the 2 bearing trees. I remove this post and set a post, 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. marked 1/4 S on N. face; from which
A Laurel 7" dia., bears N.30°E., 26 lks. dist. mkd. 1/4 S BT
A Pine 8" dia., bears S.5°W., 9 lks. dist. mkd. 1/4 S BT.

George J. Wenderoth, Deputy Co. Surveyor - Wit: Frank Loso - June 1950 - C.S. File 45/229

Set halfway between sec. corners.
Set a 1" I.Pipe for the corner, from which
A 12" Fir bearing N.39°40'E., 18.9 ft.
A 10" Fir bearing S.71°24'E., 12.3 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan/Feb. 1966 - C.S. File 52/63-69

Found - Iron pipe at 1/4 corner.
12" Fir, now dead, N.39 1/2°E., 18.9 ft. scribe visible "1/4".
10" Fir now blow down, S.71 1/4°E., 12.3 ft.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R
1/4 S 34 3
S 3 W
T 32 S
1966
New BTs- 18" D.Fir N.28°W., 23.0 ft. scribed 1/4 S34 CS BT.
7" W.Fir S.71 1/2°W., 18.8 ft. scribed 1/4 S3 CS BT.

Leonard Herzstein, U.S.F.S. (Deputized by DCSO) - Wit: Jim Hamilton - Nov. 24, 1981 - C.S. File 61/29-34

CONDITION REPORT ONLY
(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 34; & 3, T32-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Found - 1 1/4" I.P., firmly set, projecting 8" above ground with properly mkd. brass cap, with 1 1/2" I.P. alongside.
12" Fir now a root hole, bears N.39 1/2°E., 18.9 ft. (Rec. N.39°40'E.) with 12" D.Fir log alongside with fragmentary scribe marks visible on partly healed double blaze.
10" Fir now a root hole bears S.71 1/2°E., 12.3 ft. (Rec. S.71°24'E.) with rotten log alongside with no marks visible.
18" D.Fir now 18" D.Fir bears N.28°W., 23.8 ft. with healed double blaze.
7" W.Fir now 9" W.Fir bears S.71 1/2°W., 18.8 ft. with healed double blaze.

Survey by James Artman, RLS #2268 - Dec. 1990 - C.S. File 63/124-3

Found - 1" Iron pipe with 2 1/2" brass cap, 10" above ground, properly marked.
Root hole N.39 1/2°E., 18.6 ft., 12" D.Fir, down and rotted.
Root hole S.71 1/2°E., 12.3 ft., 10" D.Fir, down and rotted.
20" D.Fir N.28°W., 23.8 ft., healed blazes.
10" W.Fir S.71 1/2°W., 18.8 ft., dead, healed blazes.
1 1/2" Iron pipe alongside brass capped pipe.
New BT - 8" W.Fir S.21°W., 13.9 ft. scribed "1/4 S3 BT" nailed alum. washer mkd. "Artman RLS 2268" flush to BT face.