

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7736)

-----  
Set a Fir post 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. marked 1/4 S on N. face, from which  
A Fir 32" dia., bears N.46 1/2°W., 9 lks. dist. mkd. 1/4 S BT.  
A Fir 6" dia., bears S.15 1/4°E., 30 1/2 lks. dist. mkd. 1/4 S BT.

George J. Wenderoth, Deputy Co. Surveyor - Wit: Donald Snyder - Nov. 1946 - C.S. File 45/229

-----  
Find old BT, a 36" Fir N.46°30'W., 5.94 ft.  
Drive 2" Pipe for corner.  
Mark New BT - A 28" Fir S.24°48'W., 53.8 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby and Wm. Stoffel, crew - June 1963 - C.S. File 52/63-3

-----  
Found - 2" I.P. at corner.  
30" R.Fir, now stump - S.W., shows scribing.  
40" R.Fir N.46°30'W., 5.9 ft., now down, shows scribing.  
New BTs- 11" R.Fir bears S.3°E., 73.8 ft. scribed 1/4 S34 CSBT  
6" R.Fir bears N.69°E., 33.5 ft. scribed 1/4 S27 CSBT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-37

-----  
Found - I.Pipe at 1/4 corner.  
11" R.Fir now 12", S.3°E., 73.8 ft., shows good scars, "1/4" scribe.  
6" R.Fir now 7", N.69°E., 33.5 ft., shows good scars.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 3 W  
1/4 S 27  
S 34  
1965

Both BTs in good condition.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 7/16/25 - C.S. File 67/60-53

-----  
Found - D.C.S.O. brass cap proj 6", 2" iron pipe.  
26"x7' tall sawn D.Fir stump S.6°E. 73.8 ft (Rec S.2°E) Fully healed double blaze.

Continued next page

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

11" D.Fir N.65°E. 33.5 ft (Rec N.69°E.) Fully healed double blaze.  
Add 3½" mag nail right side center of both BTs.  
New - 6"x2½' sawn D.Fir stump S.54°W. 16.2 ft 3½" mag nail to center.  
13" D.Fir N.81°W. 24.8 ft scribed "¼ S 27 BT" on double blaze.  
Notes - Mon on gentle south slope forested to north. New clearcut south. Mon is approx 275 ft east of gravel road  
Compass decl. 14¼°E.  
OGRS COORDINATE SYSTEM  
COTTAGE GROVE-CANYONVILLE ZONE  
42°50'31.44518" N.  
123°02'33.63708" W.