

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7740)

-----  
Set a stone 11x10x5 ins., 6" in the ground, for 1/4 sec. cor. mkd. 1/4 on N. face; from which

A Laurel 11" dia., bears N.10 1/4°W., 45 lks. dist. mkd. 1/4 S BT.

A Cedar 6" dia., bears S.7°W., 25 lks. dist. mkd. 1/4 S BT.

Survey by Norman D. Price - For: W.A. McKenzie, Tiller, Oregon - April 5-18, 1955 - C.S. File 41/372

-----  
Monumented with a basalt stone, 8x4x6 ins. above ground, firmly set, mkd. 1/4 on N. face; from which the original bearing trees:

A Madrona 16" dia., bears N.10 3/4°W., 45 lks. dist., blaze healed.

An Incense Cedar 22" dia., bears S.7°W., 24 lks. dist., with blaze healed.

Against South side of stone, SET an iron post 3 ft. by 1 1/2" dia., 28" in the ground mkd. RS33.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan. 1966 - C.S. File 52/63-77

-----  
Found - Iron pipe and stone mkd. 1/4.

Orig. 16" Laurel snag, N.10 3/4°W., 29.7 ft., opened for faint scribing, rotten, not legible.

Orig. 22" Cedar now 27", S.7°W., 15.8 ft., shows scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

1/4 S 15

S 22

1966

New BT - 13" Laurel N.46°E., 23.0 ft. scribed 1/4 S15 CS BT.

Reblaze and rescribe:

27" Cedar S.7°W., 15.8 ft. scribed 1/4 S22 CS BT.

Survey by Howard Johnstone - For: Roseburg Lumber Co. - Nov. 17, 1982 - C.S. File 58/188-4

-----  
Found - 1966 DCSO brass cap and iron pipe.

A 1" Iron pipe.

30" Cedar S.7°W., 15.8 ft. (Orig. BT) rescribed.

13" Laurel N.46°E., 23.0 ft., down.

New BT - 5" Fir N.24°W., 14.4 ft.

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by Mark F. Smalley - For: Roseburg Forest Products -  
June 1, 1994 - C.S. File 63/154-15

-----

Found - DCSO brass cap with iron pipe and original stone.  
New BT - 12" Madrone N.26°E., 35.1 ft. scribed "¼ BT".  
No other live trees available within 100 ft.  
Corner lies 90 ft. East of new road centerline. Area was  
burned 5 or 6 years ago.