

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM resurvey by John Jelley, Cadastral Surveyor, Group #555, surveyed July/Aug 1964 - (DCSO records Vol. 33 Page(s) 13832)

-----  
Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line.  
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:  
T 31 S R 3 W  
C 1/4 S 10  
1964

from which

A Pine 11" dia., bears S.81°E., 41 lks. dist., mkd. C 1/4 S10 BT.

A Pine 10" dia., bears S.13°W., 30 lks. dist., mkd. C 1/4 S10 BT.

BLM Rehabilitation by Timothy J. Moore, Cadastral Surveyor, under Group #1000, surveyed Oct. 26, 2000. (DCSO rec. Vol. 53 page(s) 20605-6)

-----  
The center 1/4 sec. cor. of sec. 10, monumented with an iron post, 2 1/2" diam., firmly set, projecting 4" above ground, with brass cap mkd.  
T 31 S R 3 W  
C 1/4 S 10  
1964

from which the remains of the original bearing trees

A burnt stump, 15" dia., bears S.81°E., 27.1 ft., no scribe marks visible.

A burnt stump, 12" dia., bears S.13°W., 19.8 ft., no scribe marks visible.

and new accessories

A stainless steel post, 28" long, 2 1/2" diam., set 25" in the ground for a reference monument, bears N.39°E., 18.6 ft., with brass cap mkd. RM T31S R3W C1/4 S10 18.6 FT TO COR 2000 and an arrow pointing to the corner.

A stainless steel post, 28" long, 2 1/2" dia., set 26" in the ground for a reference monument, bears N.42 1/2°W., 13.4 ft., with brass cap mkd. RM T31S R3W C1/4 S10 13.4 FT TO COR 2000 and an arrow pointing to the corner.