

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7745)

Set a Fir post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face; from which
A Laurel 17" dia., bears South 71½ lks. dist. mkd. ¼ S BT.
A Laurel 8" dia., bears N.86°W., 74 lks. dist. mkd. ¼ S BT.
April 24, 1894

BLM resurvey by John Jelley, Cadastral Surveyor, Group #555, surveyed July/Aug 1964 - (DCSO records Vol. 33 Page(s) 13831)

The ¼ sec. cor., determined at record distance from the original bearing trees:

A Madrone clump, bears N.89°W., 74 lks. dist. (Rec. bearing N.86°W.)

A Madrone 26" dia., bears South, 71½ lks. dist., with scribe marks 4 BT visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 3 W

¼ $\frac{S \ 3}{S \ 10}$
1964

from which new bearing trees

A Fir 19" dia., bears N.70°E., 6½ lks. dist. mkd. ¼ S3 BT

A Fir 15" dia., bears S.38½°W., 21 lks. dist. mkd. ¼ S10 BT.