

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 34 & 35 only, T30-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6777)

-----  
Set a Fir post 4 ft. long, 4" sq., 24" in the ground for closing the cor. to secs. 34 and 35, marked C C T30S R3W on N.; S35 on E.; and S34 on W. faces, with 2 notches on E. and 4 notches on W. faces, from which

A Fir 40" dia., bears N.74½°E., 68½ lks. dist. mkd. T30S R3W S35 BT.

A Laurel 14" dia., bears N.49½°W., 7 lks. dist. mkd. T30S R3W S34 BT.

A Laurel 6" dia., bears S.12°W., 31 lks. dist. mkd. T30S R3W S34 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Sept. 1958 - C.S. File 42/392-3

-----  
Determined by O.B.T.s:

42" Fir bears N.74½°E., 45.2 ft., I remarked S35 BT.

Laurel stump bears N.50°W., 4.6 ft.

10" Laurel snag, down, bears S.12°E., 22.0 ft., found scribe.

At corner point, Set 3/4" x 24" Iron pipe, from which

10" Fir bears N.69°E., 35.7 ft. mkd. S35 BT.

7" Laurel bears N.79°W., 10.5 ft. mkd. S34 T30S R3W BT.

20" Laurel bears S.8°W., 22.5 ft. mkd. S3 T31S R3W BT.

24" Laurel bears S.36°E., 18.0 ft. mkd. S3 T31S R3W BT.

Corner lies squarely on top of ridge.

So. ¼ cor. Sec. 34 bears West 2564.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-38

-----  
Found - 1" Iron pipe at sec. corner.

Orig. 42" Fir, N.74½°E., 45.2 ft., shows scar.

10" Fir now 13" N.69°E., 35.7 ft., shows good scar.

7" Laurel now 10" N.79°W., 10.5 ft. scribed T30S R3W

20" Laurel S.8°W., 22.5 ft. "BT" in wood, barks scribe.

24" Laurel S.36°E., 18.0 ft. "BT" in wood, bark scribe.

Set Brass cap at cor. alongside iron pipe, mkd:

County Surveyors Office

T30S R3W

S34 | S 35

S 3

T31S R3W

1965

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 447700

PRIMARY CORNER DESCRIPTION C C for Secs. 34 & 35, T30-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Reblazed and scribed:  
24" Laurel S.36°E., 18.0 ft. mkd. T31S R3W S3 CS BT.  
Corner lies on top of ridge.

FD OK by Howard Johnstone, Aug. 1983, M 95-6

Cor. Fd and used in BLM resurvey by Wayne L. Rogers; Lance J. Bishop; James L. White, Cadastral Surveyors, under Group #1133 - Surveyed June 7, 1983/Dec. 12, 1984 - (DCSO records Vol. 47 Page(s) 17848)

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-19 A-E; revised by M166-45 A-E

-----

Found - 2½" brass stamped County Surveyor Office 1965  
BTs - 27" Madrone with tag dated 12/65; S.36°E., - 18.0'  
36.5" Fir with healed "X" set tag dated 4/14;  
S.55°W., 27.4' to nail side center  
20" Madrone with tag dated 12/65; N.75°W., 10.5'