

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 500120

PRIMARY CORNER DESCRIPTION S 1/16 Secs. 34 & 35

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

George Wenderoth, Deputy Co. Surveyor - Wit: Frank Loso -
Feb. 1948 - C.S. File 45/229

Set - 1" I.Pipe
18" W.Fir S.35°32'W., 10.5
24" N.16°45'E., 23.7

Glenn S. Baughman - For: Forest Service - April 1969 - C.S.
File 55/114 and M 37-60 (Typed from both CS file & Map)

Set - 2"x30" gal. iron pipe with brass cap marked "S1/16,
S34, 35, T31S R3W OLS 536 1969" 26" in the ground.
7" D.Fir "S1/16 S34 BT" which bears N.52½°W., 16.3 ft.
Placed BT tag.
7" Laurel "S1/16 S35 BT" which bears N.43½°E., 37.0 ft.
Placed BT tag.

Shown on Map -
1" IP set by Wenderoth (1948) bears S.2°50'04"W., 4.83'
(from set BC.)

Wenderoth's BT (from 1" IP) -
24" D.Fir bears N.17°E., 23.7'
Other BT destroyed (from CS file)

Leonard Herzstein, U.S.F.S. (Deputized by DCSO) - Wit: R.
Riley; A. Arciniega - Aug. 8, 1980 - C.S. File 61/11-14

Found - 2" dia., IP set by Baughman (OLS 536) in 1969,
firmly set, projecting 6" above ground with brass
cap (properly) mkd.
1" dia., IP set by Wenderoth (OLS 5) in 1948, firmly
set, projecting 5" above ground, bears S.2°W.,
4.8 ft. from BC.

BTs marked by Wenderoth in 1948, from 1" dia., IP -
26" dia., D.Fir N.16°45'E., 23.7 ft. with healed
blaze now bears N.19½°E., 19.8 ft. from BC.
Roothole, S.35°32'W., 10.5 ft. with W.Fir, size
indeterminate, alongside with no marks visible,
now bears S.16°W., 15.6 ft. from BC.

BTs marked by Baughman in 1969 from BC -
12" mad. snag, N.43½°E., 37.0 ft. with partial
scribe marks visible on partly healed double
blaze.
12" dia., D.Fir, N.52½°E., 16.3 ft. with healed
double blaze.
Compass decl. 18¾°E.