

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7720)

-----  
A Laurel tree, 4" dia., which I mark  $\frac{1}{4}$  S on W. face, for  $\frac{1}{4}$  sec. cor., from which

A Fir 6" dia., bears N.67 $\frac{1}{2}$ °W., 9 lks. dist. mkd.  $\frac{1}{4}$  S BT.

A Laurel 5" dia., bears S.63 $\frac{1}{2}$ °E., 3 $\frac{1}{2}$  lks. dist. mkd.  $\frac{1}{4}$  S BT.

George Wenderoth, Deputy Co. Surveyor - Wit: Frank Loso - Feb. 1948 - C.S. File 45/229

-----  
Found - 14" Fir N.67 $\frac{1}{2}$ °W., 5.9 ft.

Drive 1" Iron pipe and mark BTs:

16" Fir N.31°10'E., 29.0 ft.

14" Fir N.32°50'W., 17.5 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan/Feb. 1966 - C.S. File 52/63-86

-----  
Found - Orig. 14" now 15" Fir, N.67 $\frac{1}{2}$ °W., 5.9 ft. Tree had been opened, scribe visible "S".

16" Fir, blow down, N.31°E., 29.0 ft.

14" Fir, now snag, N.33°W., 17.5 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

$\frac{1}{4}$  S34|S35

1966

New BT - 12" D.Fir N.20°E., 46.0 ft., scribed.

Glenn S. Baughman - For: Forest Service - April 1969 - C.S. File 55/114 & M 37-60 (added 7/10/2014 - Typed from CS File)

-----  
Found - 1" gal. IP with brass cap (properly mkd) 1" IP along side.

15" D.Fir bears N.67 $\frac{1}{2}$ °W., 5.9 ft. opened & scribe visible. Tree is dying.

14" D.Fir snag N.33°W., 17.5 ft. scar.

16" Fir N.31°E., 29.0 ft. Blow down, scar.

12" D.Fir N.20°E., 46.0 ft. visible scribe, tree in good condition.

All trees except the snag have BT tags.