

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7729-30)

-----  
Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 2, 3, 10 and 11, marked T31S S2 on NE.; R3W S11 on SE.; S10 on SW.; and S3 on NW. faces, with 2 notches on E. and 5 notches on S. edges; from which  
A Dogwood 10" dia., bears N.78°E., 75 lks. dist. mkd. T31S R3W S2 BT.  
A Cedar 7" dia., bears S.25¼°E., 36½ lks. dist. mkd. T31S R3W S11 BT.  
A Cedar 12" dia., bears S.63 3/4°W., 42½ lks. dist. mkd. T31S R3W S10 BT.  
A Fir 33" dia., bears N.59°W., 18¼ lks. dist. mkd. T31S R3W S3 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd; Vern Killian - May 13, 1959 - C.S. File 42/392-15

-----  
Determined by O.B.T.s:  
10" Cedar S.25°E., 24.0 ft., found scribe.  
30" Cedar S.60°W., 28.0 ft.  
40" Fir uproot, N.59°W., 12.0 ft.  
At corner point, Set 2" x 2" wood post, from which  
4" Fir bears S.62°E., 3.7 ft. mkd. S11 BT.  
3" Fir bears S.84°W., 15.5 ft. mkd. S10 BT.  
6" Fir bears S.10°W., 33.2 ft. mkd. S3 T31S X BT.  
12" Chinquapin bears N.16°E., 62.0 ft. mkd. S2 T31S R3W BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone, Mike Darby & Wm. Stoffel, crew - June 1964 - C.S. File 52/63-8

-----  
Found - Wooden stake set by Markham.  
Incense Cedar, now 14" dia., S.25¼°E., 24.0 ft., good scribing "3W S11" visible on previously opened scar.  
Incense Cedar now 30" dia., S.63 3/4°W., 28.0 ft. Shows good axe scars.  
33" Fir N.59°W., 12.0 ft. uprooted and down.  
No trace found of original NE. tree.  
All trees mkd. by Markham in 1959 are alive and in good condition:  
4" Fir S.62°E., 3.7 ft.  
(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

3" Fir S.84°W., 15.5 ft.  
6" Fir N.10°W., (not S.10°W.) 33.2 ft.  
12" Chinquapin N.16°E., 62.0 ft.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 3 W  
S 3 | S 2  
S 10 | S 11  
1964  
Drive Markham's stake alongside.  
No new trees scribed.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #555, surveyed July/Aug 1964 - (DCSO records Vol. 33 Pgs 13826-27)  
-----  
The Sec. cor., recorded and remonumented by Markham in 1959, with a wood stake, 2" sq., 48" above the ground, firmly set, subsequently remonumented by Godfrey in 1964 with an iron pipe 1" dia., 14" above the ground, firmly set, with 1964 brass cap attached, from which the remaining original bearing trees:  
A Cedar 13" dia., bears S.25¼°E., 38½ lks. with scribe marks 3W S11 visible on opened blaze. (Rec., 36½ lks.)  
A Cedar 31" dia. bears S.63¾°W. 42½ lks with healed blaze  
A down and rotted Fir, size indeterminate, bears N.59°W., 18¼ lks.  
and bearing trees mkd. by Markham:  
A Chinquapin 16" dia., bears N.16°E., 93 lks. with scribe marks R3W 31 S visible on partially healed blaze.  
A Fir 6" dia., bears S.62°E., 5¾ lks. with illegible scribe marks visible on partially healed double blaze.  
A Fir 6" dia., bears S.84°W. 23 lks. with illegible scribe marks visible on partially healed double blaze.  
A Fir 10" dia., bears N.10°W., 50 lks. with scribe marks S visible on partially healed double blaze.  
Add marks BLM 1964 to bottom of brass cap.  
Corner is located at the SW. corner of a logged area.

James Klein - Keith Primm - Douglas Popham - For:  
Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I  
-----  
Found - 2½" brass cap stamped COUNTY SURVEYORS OFFICE 1964  
BLM 1964  
17" fir with healed face and BLM tag 1964 S.65°E., 3.6'  
24" cedar with healed face and BLM tag 1964 S.25°E., 25.6' 4)  
19.5" fir with healed face re-set tag dated 10/31/13  
S.84°W., 15.2' to nail side center cont. next pg

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

<p>16.5" fir with healed face re-set tag dated 10/31/13 N.10°W., 33.0' to nail side center New BT - 30" Hemlock (mkd: T31S R3W S2 BT) set tag dated 10/13 N.14°E., 41.25' to nail side center</p>
<p>Greg Lang - 1/17/2016 - C.S. File 65/95-13 ----- Found - Douglas County brass cap set in 1964. 16" Fir bears N.9½°W., 32.60 ft. (scribed by Markham in 1959) 18" Fir bears S.86°W., 15.00 ft. (scribed by Markham in 1959) 26" Chinquapin bears N.16½°E., 61.00 ft. (scribed by Markham in 1959) 15" Fir bears S.63°E., 3.80 ft. (scribed by Markham in 1959) 22" Cedar bears S.23°E., 25.10 ft. (original—scribed by Bushey in 1893) 30" Hemlock bears N.13°E., 41.25 ft. (scribed in 2013 per county record) New - BT tags as needed; steel post at corner. Note - Corner lies near the foot of a northeast slope; about 500 ft West of creek.</p>
<p>3</p>