

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & 2 of T32-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7689)

Set ¼ sec. post, from which
A Laurel 6" dia., bears North 3 lks.
A Laurel 5" dia., bears South, 3 lks.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7718)

The ¼ sec. cor. which is a post, greatly decayed, marked ¼ S on N. face, I find the 2 bearing trees. At cor. point, I SET a stone, 12x9x8 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on N. face; from which
A Laurel 6" dia., now 8", bears North 3 lks. mkd. ¼ S BT.
A Laurel 5" dia., bears South 3 lks. mkd. ¼ S BT.

Reported as not found 2/1966 DCSO C.S. 54/20-37A

Survey by Glenn S. Baughman - For: Forest Service - April 1969 - C.S. File 55/114 and M 37-60

Original survey by Byars and resurvey by Bushey, no evidence found.
Set 2" x 30" galv. Iron pipe with brass cap 26" in the ground, mkd. OLS 536 T31S R3W ¼ $\frac{S\ 35}{S\ 2}$
T32S
1969
Scribed- 18" D.Fir "¼ S35 BT" bears N.46½°E., 27.7 ft. placed BT tag.
10" D.Fir "¼ S2 BT" which bears S.20°E., 45.1 ft., placed BT tags.