

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7721-22)

-----  
Set a stone 15x12x6 ins., 10" in the ground for 1/4 sec. cor. marked 1/4 on N. face; from which  
A Laurel 10" dia., bears N.6 3/4°E., 30 lks. dist. mkd. 1/4 S BT.  
A Fir 12" dia., bears S.11 1/2°W., 32 lks. dist. mkd. 1/4 S BT.

George Wenderoth, Deputy Co. Surveyor - Nov. 1948 - C.S. File 45/230

-----  
Stone for corner gone. Found both BTs in good shape. Drive 1" I.Pipe for corner, from which  
24" Fir S.11°30'W., 21.1 ft.  
14" Madrona N.6°45'E., 19.8 ft.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - June 28, 1961 - C.S. File 42/392-73

-----  
Determined by O.B.Ts:  
16" dead Laurel N.7°E., 19.8 ft.  
22" Fir, uproot, S.11°W., 21.1 ft.  
At corner point found 3/4" Iron pipe, from which  
12" Fir bears N.35°W., 50.0 ft. mkd. 1/4 S26 BT.  
11" Cedar bears S.74°W., 85.0 ft. mkd. 1/4 S35 BT.  
10" Laurel bears N.66°E., 46.0 ft. mkd. 1/4 S26 T31S R3W BT.  
5" Fir bears S.26°E., 52.0 ft. mkd. 1/4 S BT.  
North end of 18" steel culvert under main road bears S.74°E., 150.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan/Feb. 1966 - C.S. File 52/63-61

-----  
Found - 3/4" Iron pipe.  
12" Fir now 15", N.35°W., 50.0 ft. scribed "1/4 S26 BT", badly burned.  
11" Cedar now 12", S.74°W., 85.0 ft. scribing visible "1/4 S35 BT".  
10" Laurel, dead, N.66°E., 46.0 ft.  
5" Fir, dead, S.26°E., 52.0 ft. scribed "1/4 S BT".

Set Brass cap alongside iron pipe, at sec. cor. marked

County Surveyors Office

T 31 S R 3 W

1/4 S 26  
S 35

1966

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New BTs- 13" D.Fir N.30°E., 116.4 ft. scribed "¼ S26 CS BT"  
22" Fir stump S.24°W., 21.4 ft. scribed "¼ S35 CS  
BT".  
Reblazed and rescribed:  
15" D.Fir N.35°W., 50.0 ft. scribed "¼ S26 CS BT".  
This corner is on skid road in middle of cutting unit.

Kris DeGroot - For Roseburg Resources Co. - 5/2010 - M157-24  
-----  
Lat: 42°50'31.613988"N. Long: 123°01'21.943538"W.  
Found DCS0 BCIP and accessories per PLSS 540200