

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7726)

Set a Fir post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face; from which
A Fir 6" dia., bears S.19½°W., 16½ lks. dist. mkd. ¼ S BT
A Hemlock 4" dia., bears N.12 ¾°E., 10½ lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Nov. 18, 1959 - C.S. File 42/392-42

Determined by O.B.T.:
24" Fir S.19°W., 10.6 ft.
At corner point, Set ¾" x 30" Iron rod, from which
7" Fir N.51°W., 22.6 ft. "¼ S14 BT".
6" Fir S.61°W., 12.3 ft. "¼ S23 BT".
15" Cedar N.82°E., 9.8 ft. "¼ S14 BT".

Gerald Nygren - For: Roseburg Resource Co. - 9/2015 - M170-10

Set - 5/8"x30" iron rod with yellow plastic cap mkd "NYGREN PLS1035"
6" D.Fir bears S.7°E., 6.1' (burnt) no scribe, BT tag on face and spike in side center at base.
8" D.Fir bears N.18°W., 21.9' (burnt) no scribe, BT tag on face and spike in side center at base.
6" D.Fir bears N.17°E., 16.4' (burnt) no scribe, BT tag on face and spike in side center at base.
9" Hemlock bears S.85°E., 12.8' (burnt) no scribe, BT tag on face and spike in side center at base.