

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7728)

Set a stone 10x10x8 ins., 6" in the ground for 1/4 sec. cor. marked 1/4 on N. face; from which

A Fir 40" dia., bears N.71 3/4°E., 29 3/4 lks. dist. mkd. 1/4 S BT.

A Fir 36" dia., bears S.13 1/4°W., 11 1/2 lks. dist. mkd. 1/4 S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Sept. 29, 1959 - C.S. File 42/392-30

Determined by O.B.T.:

50" Fir, uproot, bears N.72°E., 19.8 ft., found scribe.

At corner point, Set 3/4" x 30" Iron pipe, from which

13" Fir bears S.67°W., 16.5 ft. mkd. 1/4 S14 BT.

8" Fir bears N.38°W., 13.0 ft. mkd. 1/4 S11 BT.

8" Laurel bears N.34°E., 13.5 ft. mkd. 1/4 S11 T31S R3W BT

6" Alder bears N.55°E., 46.0 ft. mkd. 1/4 S11 BT.

Creek bears East, 40.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 14, 1965 - C.S. File 52/63-21

Found - 13" Fir now (?), S.67°W., 16.5 ft., tree down.

8" now 9" Fir N.38°W., 13.0 ft., shows partial scribing.

8" now 9" Laurel N.34°E., 13.5 ft. scribed T31S R3W S11 BT.

8" now 10" Alder N.55°E., 46.0 ft., shows partial scribing.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

1/4 $\frac{S\ 11}{S\ 14}$

1965

Set brass cap alongside Iron pipe.

New BT - 14" Fir S.29°W., 41.5 ft. scribed 1/4 S14 CS BT.

Ron Quimby - Crew: N. Fromdahl & R. Olson - 8/2015 - C.S. File 65/89-37

Found - Brass cap (properly mkd)

18" fir N.38°W., 13.0 ft. good scar.

14" laurel N.34°E., 13.5 ft. good scar.

New - 5/8" I.Rod S.35°E., (in alder clump)

continued next page

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

5/8" I.Rod N.37°W., 12.0 ft. (up 1.0)
5/8" I.Rod S.78°W., 26.0 ft. (up 1.0)
All rods have yellow plastic caps stamped ie engineering
Note - Corner is approx. 40' west of creek
Compass decl. 15½°E.