

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7731)

Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor. marked 1/4 S on N. face; from which
A Laurel 12" dia., bears S.31 1/4°W., 23 1/2 lks. mkd. 1/4 S BT.
A Fir 14" dia., bears N.28 3/4°E., 38 1/2 lks. mkd. 1/4 S BT.

Survey by John H Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - May 4, 1959 - C.S. File 42/392-16

Determined by O.B.T:
30" Fir bears N.29°E., 25.4 ft., found scribe.
At Corner point, Set 3" x 3" wood post, from which
20" Laurel bears S.4°E., 74.5 ft. mkd. 1/4 S11 BT.
12" Laurel bears S.25°E., 44.0ft. mkd. 1/4 S11 BT.
5" Fir bears S.77°E., 47.7 ft. mkd. 1/4 S11 BT.
10" Fir bears N.86°W., 73.0 ft. mkd. 1/4 S2 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 8, 1965 - C.S. File 52/63-14

Found - 20" now 29" Laurel, S.4°E., 74.5 ft. scribing visible.
12" Laurel now 14", S.25°E., 44.0 ft. scribing visible.
5" Fir now 8", S.77°E., 47.7 ft., shows good scar.
10" Fir now 15", N.86°W., 73.0 ft., scribed.
(All BTs recorded by Markham)

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 3 W
1/4 S 2
S 11
1965

All bearing trees in good condition, did not mark new BTs.

Greg Lang - 1/14/2016 - C.S. File 65/95-12

Found - Brass Cap set by DCSO in 1965.
22" Fir bears S.76 1/2°E., 47.20 ft (47.7 ft). (scribed by Markham in 1959)
32" Laurel bears S.1 1/2°E., 70.70 ft (74.5 ft) (scribed by Markham in 1959)
New - Set 5/8" iron rod with plastic cap marked "Lang Surveying" as a bearing object; said point bears easterly (on section line) 22.40 feet from the brass cap. Steel post with tag set alongside
continued next page

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set 5/8" iron rod with plastic cap marked "Lang Surveying" as a bearing object; said point bears westerly (on section line) 44.50 ft from the brass cap. Steel post with tag set alongside BT tags as needed; steel post at the corner.

Note - Corner lies on open North slope, 100 ft easterly of creek.