

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 547700

PRIMARY CORNER DESCRIPTION C C for Secs. 35 & 36, T30-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6775-76)

Set a Cedar post 4½ ft. long, 4" sq., 24" in the ground for closing cor. to secs. 35 and 36, marked C C T30S R3W on N.; S36 on E.; and S35 on W. faces, with 1 notch on E. and 5 notches on W. faces, from which
A Cedar 10" dia., bears N.57½°E., 17¼ lks. dist. mkd. T30S R3W S36 BT.
A Cedar 10" dia., bears N.51°W., 12 ¾ lks. dist. mkd. T30S R3W S35 BT.
A Cedar 12" dia., bears S.42°E., 4½ lks. dist. mkd. T30S R3W S35 & 36 C C BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - April 29, 1959 - C.S. File 42/392-12

Determined by O.B.T.s:
11" Cedar N.56°E., 11.3 ft., found scribe.
13" Cedar N.51°W., 12.0 ft.
At corner point, SET ¾" x 30" Iron pipe, from which
14" Laurel S.80°E., 23.0 ft. mkd. S2 BT.
12" Laurel N.77°E., 33.0 ft. mkd. S36 T30S R3W BT.
10" Cedar N.7°E., 44.4 ft. mkd. S36 BT.
12" Laurel bears N.75°W., 44.4 ft. mkd. S35 T30S R3W BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-26

Found - No trace of I.Pipe as recorded by Markham.
Orig. 11" now 13" Cedar N.56°E., 11.3 ft., scribe visible.
Orig. 13" Cedar, now down, N.51°W., 12.0 ft.
12" now 13" Laurel N.75°W., 44.4 ft., bark scribed.
12" now 13" Laurel N.77°E., 33.0 ft., bark scribed.
14" now 15" Laurel S.80°E., 23.0 ft. scribed S2 BT.
10" Cedar N.7°E., 44.4 ft. scribe visible S36 BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 3 W
S 35 | S 36
S 2
T 31 S R 3 W
1965
New BT - 24" D.Fir N.65½°W., 21.0 ft. scribed T30S R3W S35 CS BT.

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 547700

PRIMARY CORNER DESCRIPTION C C for Secs. 35 & 36 only, T30-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Wayne L. Rogers; Lance J. Bishop; James L. White, Cadastral Surveyors, under Group #1133 - surveyed June 7, 1983/Dec. 12, 1984 - (DCSO records Vol. 47 Page(s) 17846)

The Cor. of Secs. 35 & 36 only, perpetuated and recorded by Markham in 1959, and further perpetuated and recorded by Powell in 1965, monumented with an iron post, 1¼" dia., firmly set, projecting 4" above ground, with 1965 brass cap. from which the remaining original bearing tree:

A Cedar 23" dia., bears N.57¼°E., 17¼ lks. dist., with healed blaze.

and remains of bearing trees mkd. by Markham:

A Cedar 14" dia., bears N.7°E., 67 lks. dist, with scribe marks S36 BT visible on partially healed blaze.

A Madrone 19" dia., bears S.80°E., 35 lks. dist., with healed blaze.

A Madrone stump 13" dia., bears N.75°W., 67 lks. dist., no marks visible.

and the remains of a bearing tree mkd. by Powell:

A sawed Fir stump 24" dia., bears N.65½°W., 32 lks. dist., with healed blaze.

and a new bearing tree:

A Cedar 9" dia., bears N.32°W., 208 lks. dist., mkd. T30S R3W S35 BT.