

PRIMARY CORNER DESCRIPTION Sec Cor for 35 & 36; 1 & 2, T32-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7689)

-----  
 Set post cor. to secs. 1, 2, 35 and 36, from which  
 No tree in sec. 36 in limits.  
 A Pine 30" dia., bears S.62°E., 105 lks. dist.  
 A Laurel 8" dia., bears S.50°W., 57 lks. dist.  
 A Pine 30" dia., bears N.42°W., 115 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7694)

-----  
 The Sec. cor. is destroyed by fire. I find 2 of the witness trees. At cor. point, Set a stone 15x11x7 ins., 10" in the ground for corner, marked with 1 notch on E. and 5 notches on W. edges; from which  
 A Laurel 8" dia., now 10", bears S.50°W., 57 lks. dist. mkd. T32S R3W S2 BT.  
 A Pine 30" dia., bears N.42°W., 115 lks. dist. mkd. T31S R3W S35 BT.  
 These are the original witness trees.  
 The Laurel in sec. 2 is broken off 10 ft. above the ground.  
 The Pine in Sec. 1 is destroyed by fire. I mark 2 new witness trees as follows:  
 A Pine 12" dia., bears S.12½°E., 270 lks. dist. mkd. T32S R3W S1 BT.  
 A Pine 14" dia., bears S.31°W., 160 lks. dist. mkd. T32S R3W S2 BT.  
 No tree in sec. 36 in limits.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, Mike Stone; Jack Heritage, crew -April 1966 - C.S. File 52/63-95

-----  
 No trace of corner stone.  
 Found - 10" Laurel S.50°W., 37.6 ft., no trace of this tree.  
 30" Pine now 53", N.42°W., 75.9 ft., scribe visible "35".  
 12" Pine now 38", S.12½°E., 178.2 ft., shows scar.  
 14" now 31" Pine S.31°W., 105.6 ft., scribe visible "2".

Set Brass cap at cor. mkd: County Surveyors Office

	T	31	S	
S	35		S	36
S	2		S	1
	1966			

R3W

(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

New BTs- 8" Laurel S.42°E., 26.9 ft. scribed T31S R3W S1 CSBT  
6" Laurel N.68°E., 5.2 ft. scribed T31S R3W S36 CS  
BT.  
Reblazed and rescribed:  
53" Pine N.42°W., 75.9 ft. scribed T31S R3W S35 CS  
BT.

Kris DeGroot - For: USFS - 6/2007 - C.S. File 65/60-42  
-----

Found - A 1 3/8" dia. galvanized iron post, firmly set,  
projecting 12" a 6" high x 18" dia. mound of  
stone with a 2 1/2" brass cap (properly) stamped:  
from which an original BT by Byars in 1871:  
A 49" Pine snag bears N.42°W., 77.1 ft. with scribe  
marks "W S35 CS B" visible on a partially healed  
single blaze (Rec. N.42°W., 115 lks.)  
and bearing trees by Bushey in 1893:  
A 42" Pine bears S.12 1/2°E., 178.2 ft. with a deep  
partially healed single blaze. (Rec. S.12 1/2°E.,  
270 lks.)  
A 38" Pine bears S.31°W., 105.6 ft. with a healed  
single blaze. (Rec. S.31°W., 160 lks.)  
and bearing trees by Powell in 1966:  
A 8" madrone bears N.68°E., 5.3 ft. with a healed  
single blaze. (Rec. N.68°E., 5.2 ft.)  
A 9" madrone bears S.42°E., 27.0 ft. with illegible  
scribe marks visible on a partially healed single  
blaze. (Rec. S.42°E., 26.9 ft.)  
New - A 12" D.fir bears N.56°W., 35.9 ft, scribed "T31S  
R3W S35 BT".  
Note - All new bearing trees have double blazed faces with  
a brass washer stamped "PLS 1941" nailed into the  
lower blaze. Bearings are taken to the center of  
the tree at the root crown and distances are  
measured to an aluminum nail in the root crown at  
the side and center of the tree. All bearing  
trees have a 6" red band painted around the tree  
and the blazed face painted red and BT and USFS  
Land Survey Monument sign nailed to the tree.

**See C.S. File 63/166, T32S R3W folder, for 2005 correspondence between  
USFS & the BLM concerning the subdivision of Secs 1 & 12. This files are  
not available on the internet.**

